

SULPHURIC ACID 1N SOLUTION ALPHA CHEMICALS PTY LTD

Chemwatch: 5414-22 Version No: 2.1.1.1 Safety Data Sheet according to WHS and ADG requirements Chemwatch Hazard Alert Code: 3

Issue Date: 21/07/2020 Print Date: 07/08/2020 S.GHS.AUS.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

| Product name | SULPHURIC ACID 1N SOLUTION | |
|-------------------------------|---|--|
| Synonyms | Sulphuric acid 0.5 mol/l (1 N) aqueous solution | |
| Proper shipping name | SULPHURIC ACID with not more than 51% acid or BATTERY FLUID, ACID | |
| Other means of identification | Not Available | |

Relevant identified uses of the substance or mixture and uses advised against

| Relevant identified uses | Use according to manufacturer's directions. |
|--------------------------|---|
|--------------------------|---|

Details of the supplier of the safety data sheet

| Registered company name | ALPHA CHEMICALS PTY LTD |
|-------------------------|---|
| Address | 4 ALLEN PLACE WETHERILL PARK NSW 2099 Australia |
| Telephone | 61 (0)2 9982 4622 |
| Fax | Not Available |
| Website | ~ |
| Email | shane@alphachem.com.au |

Emergency telephone number

| Association / Organisation | ALPHA CHEMICALS PTY LTD | |
|-----------------------------------|-------------------------|--|
| Emergency telephone numbers | 61 (0)418 237 771 | |
| Other emergency telephone numbers | Not Available | |

SECTION 2 Hazards identification

Classification of the substance or mixture

HAZARDOUS CHEMICAL. DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

ChemWatch Hazard Ratings

| | Min | Max | |
|--------------|-----|-----|-------------------------|
| Flammability | 0 | 1 | |
| Toxicity | 2 | | 0 = Minimum |
| Body Contact | 3 | | 1 = Low |
| Reactivity | 1 | | 2 = Moderat |
| Chronic | 3 | | 3 = High 4 = Extreme |

| Poisons Schedule | S6 | |
|-------------------------------|--|--|
| Classification ^[1] | Skin Corrosion/Irritation Category 1A, Serious Eye Damage Category 1, Carcinogenicity Category 1A | |
| Legend: | 1. Classified by Chernwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI | |

Label elements

| Hazard pictogram(s) | |
|---------------------|--|
| | |
| Signal word Danger | |

| Hazard | statement(s) |
|--------|--------------|
|--------|--------------|

| H314 | Causes severe skin burns and eye damage. |
|------|--|
| H350 | May cause cancer. |

Precautionary statement(s) Prevention

| • • • • • • | |
|-------------|--|
| P201 | Obtain special instructions before use. |
| P260 | Do not breathe mist/vapours/spray. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P281 | Use personal protective equipment as required. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |

Precautionary statement(s) Response

| P301+P330+P331 | IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. | |
|----------------|--|--|
| P303+P361+P353 | IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. | |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. | |
| P308+P313 | IF exposed or concerned: Get medical advice/attention. | |
| P310 | Immediately call a POISON CENTER or doctor/physician. | |
| P321 | Specific treatment (see advice on this label). | |
| P363 | Wash contaminated clothing before reuse. | |
| P304+P340 | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. | |

Precautionary statement(s) Storage

P405 Store locked up.

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

| CAS No | %[weight] | Name |
|-----------|-----------|------------------|
| 7664-93-9 | 1-5 | 1N Sulfuric acid |
| 7732-18-5 | >60 | Distilled Water |

SECTION 4 First aid measures

| Description of first aid measur | es |
|---------------------------------|---|
| Eye Contact | If this product comes in contact with the eyes: Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. |
| Skin Contact | If skin or hair contact occurs: Immediately flush body and clothes with large amounts of water, using safety shower if available. Quickly remove all contaminated clothing, including footwear. Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre. Transport to hospital, or doctor. |
| Inhalation | If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay. Inhalation of vapours or aerosols (mists, fumes) may cause lung oedema. Corrosive substances may cause lung damage (e.g. lung oedema, fluid in the lungs). As this reaction may be delayed up to 24 hours after exposure, affected individuals need complete rest (preferably in semi-recumbent posture) and must be kept under medical observation even if no symptoms are (yet) manifested. Before any such manifestation, the administration of a spray containing a dexamethasone derivative or beclomethasone derivative may be considered. This must definitely be left to a doctor or person authorised by him/her. (ICSC13719) |
| Ingestion | For advice, contact a Poisons Information Centre or a doctor at once. Urgent hospital treatment is likely to be needed. If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. |

- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Transport to hospital or doctor without delay.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically

- For acute or short term repeated exposures to strong acids:
 - Airway problems may arise from laryngeal edema and inhalation exposure. Treat with 100% oxygen initially.
 - ٠ Respiratory distress may require cricothyroidotomy if endotracheal intubation is contraindicated by excessive swelling
 - ٠ Intravenous lines should be established immediately in all cases where there is evidence of circulatory compromise
- Strong acids produce a coagulation necrosis characterised by formation of a coagulum (eschar) as a result of the dessicating action of the acid on proteins in specific tissues.

INGESTION

Immediate dilution (milk or water) within 30 minutes post ingestion is recommended.

- **DO NOT** attempt to neutralise the acid since exothermic reaction may extend the corrosive injury.
- Be careful to avoid further vomit since re-exposure of the mucosa to the acid is harmful. Limit fluids to one or two glasses in an adult.
- ۲ Charcoal has no place in acid management.
- Some authors suggest the use of lavage within 1 hour of ingestion.

SKIN:

Skin lesions require copious saline irrigation. Treat chemical burns as thermal burns with non-adherent gauze and wrapping.

Deep second-degree burns may benefit from topical silver sulfadiazine.

EYE:

- Eye injuries require retraction of the eyelids to ensure thorough irrigation of the conjuctival cul-de-sacs. Irrigation should last at least 20-30 minutes. DO NOT use neutralising agents or any other additives. Several litres of saline are required.
- Cycloplegic drops, (1% cyclopentolate for short-term use or 5% homatropine for longer term use) antibiotic drops, vasoconstrictive agents or artificial tears may be indicated dependent on the severity of the injury.

Steroid eye drops should only be administered with the approval of a consulting ophthalmologist).

[Ellenhorn and Barceloux: Medical Toxicology]

SECTION 5 Firefighting measures

Extinguishing media

- Water spray or fog.
- Foam.
- ٠ Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

Special hazards arising from the substrate or mixture

Fire Incompatibility None known.

Advice for firefighters

| Fire Fighting | Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water course. Use fire fighting procedures suitable for surrounding area. Do not approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. Equipment should be thoroughly decontaminated after use. |
|-----------------------|--|
| Fire/Explosion Hazard | Non combustible. Not considered to be a significant fire risk. Acids may react with metals to produce hydrogen, a highly flammable and explosive gas. Heating may cause expansion or decomposition leading to violent rupture of containers. May emit corrosive, poisonous fumes. May emit acrid smoke. Decomposition may produce toxic fumes of: sulfur oxides (SOx) |
| HAZCHEM | 2R |

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

| Major Spills | Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water course. Stop leak if safe to do so. Contain spill with sand, earth or vermiculite. Collect recoverable product into labelled containers for recycling. Neutralise/decontaminate residue (see Section 13 for specific agent). |
|--------------|---|
|--------------|---|

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

| Precautions for safe handling | |
|-------------------------------|--|
| Safe handling | DO NOT allow clothing wet with material to stay in contact with skin Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. WARNING: To avoid violent reaction, ALWAYS add material to water and NEVER water to material. Avoid smoking, naked lights or ignition sources. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers securely sealed when not in use. |
| Other information | Store in original containers. Keep containers securely sealed. Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this SDS. |

Conditions for safe storage, including any incompatibilities

| Suitable container | DO NOT use aluminium or galvanised containers Check regularly for spills and leaks Lined metal can, lined metal pail/ can. Plastic pail. Polyliner drum. Packing as recommended by manufacturer. Check all containers are clearly labelled and free from leaks. For low viscosity materials Drums and jerricans must be of the non-removable head type. Where a can is to be used as an inner package, the can must have a screwed enclosure. For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.): Removable head packaging; Cans with friction closures and low pressure tubes and cartridges may be used. - Where combination packages are used, and the inner packages are of glass, porcelain or stoneware, there must be sufficient inert cushioning material in contact with inner and outer packages unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic. |
|-------------------------|--|
| Storage incompatibility | Inorganic acids are generally soluble in water with the release of hydrogen ions. The resulting solutions have pH's of less than 7.0. Inorganic acids neutralise chemical bases (for example: amines and inorganic hydroxides) to form salts - neutralisation can generate dangerously large amounts of heat in small spaces. The dissolution of inorganic acids in water or the dilution of their concentrated solutions with additional water may generate significant heat. The addition of water to inorganic acids often generates sufficient heat in the small region of mixing to cause some of the water to boil explosively. The resulting "bumping" can spatter the acid. Inorganic acids react with active metals, including such structural metals as aluminum and iron, to release hydrogen, a flammable gas. Inorganic acids can initiate the polymerisation of certain classes of organic compounds. Reacts with mild steel, galvanised steel / zinc producing hydrogen gas which may form an explosive mixture with air. |

SECTION 8 Exposure controls / personal protection

Not Available

Control parameters

Occupational Exposure Limits (OEL)

| INGREDIENT DATA |
|-----------------|
|-----------------|

| Source | Ingredient | Material name | | TWA | STEL Peak | | | Notes |
|------------------------------|-----------------------------|----------------------|--|---------------|---------------|---------------|--------|---------------|
| Australia Exposure Standards | 1N Sulfuric acid | Sulphuric acid | | 1 mg/m3 | 3 mg/m3 | Not Available | | Not Available |
| Emergency Limits | | | | | | | | |
| Ingredient | Material name | Naterial name TEEL-1 | | | TEEL-2 | | TEEL-3 | |
| 1N Sulfuric acid | Sulfuric acid Not Available | | | Not Available | | Not Ava | ilable | |
| Ingredient | Original IDLH | | | | Revised IDLH | | | |
| 1N Sulfuric acid | 15 mg/m3 | | | | Not Available | | | |

Not Available

Distilled Water

| Appropriate engineering controls | Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure. Local exhaust ventilation usually required. |
|-------------------------------------|--|
| Personal protection | |
| Eye and face protection | Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; spectacles are not sufficient where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the material may be under pressure. Chemical goggles.whenever there is a danger of the material coming in contact with the eyes; goggles must be properly fitted. Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary protection of eyes; these afford face protection. Alternatively a gas mask may replace splash goggles and face shields. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. |
| Skin protection | See Hand protection below |
| Hands/feet protection | Elbow length PVC gloves When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots. The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended. Suitability and durability of glove type is dependent on usage. |
| Body protection | See Other protection below |
| Other protection | Overalls. PVC Apron. PVC protective suit may be required if exposure severe. Eyewash unit. Ensure there is ready access to a safety shower. |

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the *computer-generated* selection:

SULPHURIC ACID 1N SOLUTION

| Material | СРІ |
|------------------|-----|
| NEOPRENE | А |
| BUTYL | С |
| NATURAL RUBBER | С |
| NATURAL+NEOPRENE | С |
| NEOPRENE/NATURAL | С |
| NITRILE | С |
| PE | С |
| PVA | С |
| PVC | C |
| SARANEX-23 | С |
| VITON | С |

* CPI - Chemwatch Performance Index

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Respiratory protection

Type E-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

| Required Minimum Protection Factor | Half-Face Respirator | Full-Face Respirator | Powered Air Respirator |
|---------------------------------------|-------------------------|-------------------------|----------------------------|
| up to 10 x ES | E-AUS P2 | - | E-PAPR-AUS / Class 1 P2 |
| up to 50 x ES | - | E-AUS / Class 1 P2 | - |
| up to 100 x ES | - | E-2 P2 | E-PAPR-2 P2 ^ |

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

A: Best Selection

SECTION 9 Physical and chemical properties

| Appearance | Acidic liquid; mixes with water. | | | | | |
|--|----------------------------------|---|----------------|--|--|--|
| Physical state | Liquid | Relative density (Water = 1) | Not Available | | | |
| Odour | Not Available | Partition coefficient n-octanol / water | Not Available | | | |
| Odour threshold | Not Available | Auto-ignition temperature (°C) | Not Applicable | | | |
| pH (as supplied) | Not Available | Decomposition temperature | Not Available | | | |
| Melting point / freezing point (°C) | Not Available | Viscosity (cSt) | Not Available | | | |
| nitial boiling point and boiling range (°C) | Not Available | Molecular weight (g/mol) | Not Applicable | | | |
| Flash point (°C) | Not Applicable | Taste | Not Available | | | |
| Evaporation rate | Not Available | Explosive properties | Not Available | | | |
| Flammability | Not Applicable | Oxidising properties | Not Available | | | |
| Upper Explosive Limit (%) | Not Applicable | Surface Tension (dyn/cm or mN/m) | Not Available | | | |
| Lower Explosive Limit (%) | Not Applicable | Volatile Component (%vol) | Not Available | | | |
| Vapour pressure (kPa) | Not Available | Gas group | Not Available | | | |
| Solubility in water | Miscible | pH as a solution (1%) | Not Available | | | |
| Vapour density (Air = 1) | Not Available | VOC g/L | Not Available | | | |

SECTION 10 Stability and reactivity

| Reactivity | See section 7 |
|-------------------------------------|---|
| Chemical stability | Contact with alkaline material liberates heat |
| Possibility of hazardous reactions | See section 7 |
| Conditions to avoid | See section 7 |
| Incompatible materials | See section 7 |
| Hazardous decomposition products | See section 5 |

SECTION 11 Toxicological information

Information on toxicological effects

| Inhaled | Corrosive acids can cause irritation of the respiratory tract, with coughing, choking and mucous membrane damage. There may be dizziness, headache, nausea and weakness. | | |
|-------------------|--|---------------------------------|--|
| Ingestion | The material can produce severe chemical burns within the oral cavity and gastrointestinal tract following ingestion. Ingestion of acidic corrosives may produce burns around and in the mouth, the throat and oesophagus. Immediate pain and difficulties in swallowing and speaking may also be evident. | | |
| Skin Contact | The material can produce severe chemical burns following direct contact with the skin. Skin contact with acidic corrosives may result in pain and burns; these may be deep with distinct edges and may heal slowly with the formation of scar tissue. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. | | |
| Eye | The material can produce severe chemical burns to the eye following direct contact. Vapours or mists may be extremely irritating. If applied to the eyes, this material causes severe eye damage. Direct eye contact with acid corrosives may produce pain, tears, sensitivity to light and burns. Mild burns of the epithelia generally recover rapidly and completely. | | |
| Chronic | Repeated or prolonged exposure to corrosives may result in the erosion of teeth, inflammatory and ulcerative changes in the mouth and necrosis (rarely) of the jaw. Bronchial irritation, with cough, and frequent attacks of bronchial pneumonia may ensue. Repeated or prolonged exposure to acids may result in the erosion of teeth, swelling and/or ulceration of mouth lining. Irritation of airways to lung, with cough, and inflammation of lung tissue often occurs. Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. | | |
| SULPHURIC ACID 1N | ΤΟΧΙΟΙΤΥ | IRRITATION | |
| SOLUTION | Not Available | Not Available | |
| | ΤΟΧΙΟΙΤΥ | IRRITATION | |
| 1N Sulfuric acid | Inhalation (guinea pig) LC50: 0.036 mg/l/8H ^[2] | Eye (rabbit): 1.38 mg SEVERE | |
| | Oral (rat) LD50: 2140 mg/kg ^[2] | Eye (rabbit): 5 mg/30sec SEVERE | |
| . | тохісіту | IRRITATION | |
| Distilled Water | | | |

| Legend: | 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances | | | |
|---|---|--------------------------|--|--|
| | | | | |
| SULPHURIC ACID 1N SOLUTION | For acid mists, aerosols, vapours Test results suggest that eukaryotic cells are susceptible to genetic damage when the pH falls to about 6.5. Cells from the respiratory tract have not been examined in this respect. Mucous secretion may protect the cells of the airway from direct exposure to inhaled acidic mists (which also protects the stomach lining from the hydrochloric acid secreted there). | | | |
| 1N SULFURIC ACID | WARNING: For inhalation exposure <u>ONLY</u> : This substance has been classified by the IARC as Group 1: CARCINOGENIC TO HUMANS Occupational exposures to strong inorganic acid mists of sulfuric acid: | | | |
| SULPHURIC ACID 1N SOLUTION & 1N SULFURIC ACID | Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production. | | | |
| SULPHURIC ACID 1N SOLUTION & DISTILLED WATER | No significant acute toxicological data identified in literature search. | | | |
| Acute Toxicity | × | Carcinogenicity | ✓ | |
| Skin Irritation/Corrosion | ✓ | Reproductivity | × | |
| Serious Eye Damage/Irritation | × | STOT - Single Exposure | × | |
| Respiratory or Skin sensitisation | × | STOT - Repeated Exposure | × | |
| Mutagenicity | × | Aspiration Hazard | × | |
| | | | not available or does not fill the criteria for classification le to make classification | |

SECTION 12 Ecological information

Toxicity

| SULPHURIC ACID 1N SOLUTION | Endpoint | Test Duration (hr) | Species | Value | Source |
|-------------------------------|------------------|--------------------|-------------------------------|------------------|-----------------|
| | Not Available | Not Available | Not Available | Not Available | Not Availabl |
| 1N Sulfuric acid | Endpoint | Test Duration (hr) | Species | Value | Sourc |
| | LC50 | 96 | Fish | =8mg/L | 1 |
| | EC50 | 48 | Crustacea | =42.5mg/L | 1 |
| | EC50 | 72 | Algae or other aquatic plants | >100mg/L | 2 |
| | NOEC | Not Available | Crustacea | 0.15mg/L | 2 |
| | Endpoint | Test Duration (hr) | Species | Value | Sourc |
| Distilled Water | LC50 | 96 | Fish | 897.520mg/L | 3 |
| | EC50 | 96 | Algae or other aquatic plants | 8768.874mg/L | 3 |

V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Ecotoxicity:

The tolerance of water organisms towards pH margin and variation is diverse. Recommended pH values for test species listed in OECD guidelines are between 6.0 and almost 9. Acute testing with fish showed 96h-LC50 at about pH 3.5 Prevent, by any means available, spillage from entering drains or water courses.

DO NOT discharge into sewer or waterways.

Persistence and degradability

| Ingredient | Persistence: Water/Soil | Persistence: Air |
|-----------------|-------------------------|------------------|
| Distilled Water | LOW | LOW |

Bioaccumulative potential

| Ingredient | Bioaccumulation |
|-----------------|----------------------|
| Distilled Water | LOW (LogKOW = -1.38) |
| | |

Mobility in soil

| Ingredient | Mobility |
|-----------------|------------------|
| Distilled Water | LOW (KOC = 14.3) |

SECTION 13 Disposal considerations

| Waste treatment methods | |
|------------------------------|--|
| Product / Packaging disposal | DO NOT allow wash water from cleaning or process equipment to enter drains. It may be necessary to collect all wash water for treatment before disposal. In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. Where in doubt contact the responsible authority. Recycle wherever possible. Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. Treat and neutralise at an approved treatment plant. Treatment should involve: Neutralisation with soda-ash or soda-lime followed by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material). Decontaminate empty containers with 5% aqueous sodium hydroxide or soda ash, followed by water. Observe all label safeguards until containers are cleaned and destroyed. |

SECTION 14 Transport information

Labels Required



Marine Pollutant NC HAZCHEM 2R

Land transport (ADG)

| Eand transport (ADO) | | | |
|------------------------------|--|--|--|
| UN number | 2796 | | |
| UN proper shipping name | SULPHURIC ACID with not more than 51% acid or BATTERY FLUID, ACID | | |
| Transport hazard class(es) | Class 8 Subrisk Not Applicable | | |
| Packing group | I | | |
| Environmental hazard | Not Applicable | | |
| Special precautions for user | Special provisions Not Applicable Limited quantity 1 L | | |

Air transport (ICAO-IATA / DGR)

| UN number | 2796 | | |
|------------------------------|--|---|----------------|
| UN proper shipping name | Sulphuric acid with 51% or less acid | | |
| | ICAO/IATA Class | 8 | |
| Transport hazard class(es) | ICAO / IATA Subrisk | Not Applicable | |
| | ERG Code | 8L | |
| Packing group | II III III III III III III III III III | | |
| Environmental hazard | Not Applicable | | |
| | Special provisions | | Not Applicable |
| | Cargo Only Packing Instructions | | 855 |
| | Cargo Only Maximum Qty / Pack | | 30 L |
| Special precautions for user | Passenger and Cargo Packing Instructions | | 851 |
| | Passenger and Cargo Maximum Qty / Pack | | 1 L |
| | Passenger and Cargo | Passenger and Cargo Limited Quantity Packing Instructions | |
| | Passenger and Cargo | Limited Maximum Qty / Pack | 0.5 L |

Sea transport (IMDG-Code / GGVSee)

| UN number | 2796 | | |
|----------------------------|---|---------------------|--|
| UN proper shipping name | SULPHURIC ACID with not more than 51% acid or BATTERY FLUID, ACID | | |
| Transport hazard class(es) | IMDG Class IMDG Subrisk | 8 Not Applicable | |
| Packing group | II | | |
| Environmental hazard | Not Applicable | | |

| | EMS Number | F-A , S-B |
|------------------------------|--------------------|----------------|
| Special precautions for user | Special provisions | Not Applicable |
| | Limited Quantities | 1 L |

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

1N Sulfuric acid is found on the following regulatory lists

| Australia Hazardous Chemical Information System (HCIS) - Hazardous | Chemicals |
|--|-----------|
| Australian Inventory of Industrial Chemicals (AIIC) | |
| Chemical Footprint Project - Chemicals of High Concern List | |

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1 : Carcinogenic to humans

Distilled Water is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

National Inventory Status

| National Inventory | Status |
|--------------------------------|--|
| Australia - AIIC | Yes |
| Australia - Non-Industrial Use | No (1N Sulfuric acid; Distilled Water) |
| Canada - DSL | Yes |
| Canada - NDSL | No (1N Sulfuric acid; Distilled Water) |
| China - IECSC | Yes |
| Europe - EINEC / ELINCS / NLP | Yes |
| Japan - ENCS | Yes |
| Korea - KECI | Yes |
| New Zealand - NZIoC | Yes |
| Philippines - PICCS | Yes |
| USA - TSCA | Yes |
| Taiwan - TCSI | Yes |
| Mexico - INSQ | Yes |
| Vietnam - NCI | Yes |
| Russia - ARIPS | Yes |
| Legend: | Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets) |

SECTION 16 Other information

| Revision Date | 21/07/2020 |
|---------------|------------|
| Initial Date | 21/07/2020 |

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC – TWA: Permissible Concentration-Time Weighted Average PC – STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit₀ IDLH: Immediately Dangerous to Life or Health Concentrations OSF: Odour Safety Factor NOAEL: No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.