

Alitflock 4840

ADDITIVE FOR FASTRIP PAINT-STRIPPER

Alitflock 4840	<p>Alitflock 4840 is a powder additive. It is used to improve the efficiency of filtration process on paint stripping baths. In order to reduce the filtration time, this product is added "as it is" in the Metalstrip baths.</p> <p>Alitflock 4840the product has been especially developed to minimize the emission of dust in the air.</p>	
Characteristic data	Appearance	powder, granules
	Color	brown
	Density	about 0.6 g/cm ³
	Dosage	about 8 - 30 % (weight)
	Form of delivery	Alitflock 4840 12.5 kg (bucket)
	<p>The effectiveness of this product is strongly influenced by the status of unfiltered paint stripping solution. In individual cases, the optimal operating parameters may therefore lie outside the indicated standard ranges.</p>	
Safety precautions	<p>Please observe the usual safety precautions when handling chemical substances. The classifications according to the statutory regulations for transport, storage and handling of the product as well as further product specific information are included in the EC-safety data sheet.</p>	
Preparation and Procedure	<p>Alitflock 4840 is added as it is to paint stripping baths in percentages ranging from 8 to 30 %. Alitflock 4840 must be added to liquid Metalstrip solution and properly mixed. For this operation is normally used a stirrer. It is advisable to cover the mixing tank to avoid the spill and the inhalation of the powder. Please operate in safe conditions.</p> <p>The stirring time is considered finish when the mixture become homogeneous.</p> <p>The exact dosage of the Alitflock 4840 is to be sought case by case prior to our technical service's support.</p>	
Storage	<p>The Alitflock 4840 is supplied in 12.5 kg buckets and must be stored in the original packaging in dry, ventilated and indoors places, to prevent the presence of moisture causes the packing of the material, prejudicing its subsequent use.</p>	
	<p>We will be happy to provide you with our knowledge and advice to guarantee the best process quality.</p>	