

AMMONIUM METAVANADATE ALPHA CHEMICALS PTY LTD

Chemwatch Hazard Alert Code: 4

Issue Date: **27/06/2017** Print Date: **20/06/2021** S.GHS.AUS.EN

Chemwatch: 2859 Version No: 7.1.7.7

Safety Data Sheet according to WHS Regulations (Hazardous Chemicals) Amendment 2020 and ADG requirements

SECTION 1 Identification of the substance / mixture and of the company / undertaking

| Product Identifier | | |
|-------------------------------|--|--|
| Product name | AMMONIUM METAVANADATE | |
| Chemical Name | ammonium metavanadate | |
| Synonyms | H4-N-O3-V; ammonium vanadate; vanadic acid, ammonium salt; 10027 | |
| Proper shipping name | AMMONIUM METAVANADATE | |
| Chemical formula | H4NO3V | |
| Other means of identification | Not Available | |
| CAS number | 7803-55-6 | |

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses For catalyst as vanadium pentoxide, dyes, varnishes, indelible inks, drier for paints and inks, photography, analytical reagent.

Details of the supplier of the safety data sheet

| Registered company name | ALPHA CHEMICALS PTY LTD | |
|-------------------------|---|--|
| Address | ALLEN PLACE WETHERILL PARK NSW 2099 Australia | |
| Telephone | 1 (0)2 9982 4622 | |
| Fax | Not Available | |
| Website | ~ | |
| Email | shane@alphachem.com.au | |

Emergency telephone number

| Association / Organisation | ALPHA CHEMICALS PTY LTD |
|-----------------------------------|-------------------------|
| Emergency telephone numbers | 61 (0)418 237 771 |
| Other emergency telephone numbers | Not Available |

SECTION 2 Hazards identification

Classification of the substance or mixture

HAZARDOUS CHEMICAL. DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

ChemWatch Hazard Ratings

| | Min | Max | |
|--------------|-----|-----|-------------------------|
| Flammability | 0 | | |
| Toxicity | 4 | | 0 = Minimum |
| Body Contact | 2 | | 1 = Low |
| Reactivity | 0 | | 2 = Moderate |
| Chronic | 2 | | 3 = High 4 = Extreme |

| Poisons Schedule | Not Applicable | |
|-------------------------------|--|--|
| Classification ^[1] | Acute Toxicity (Oral) Category 3, Acute Toxicity (Inhalation) Category 2, Skin Corrosion/Irritation Category 2, Eye Irritation Category 2A, Germ cell mutagenicity Category 2, Specific target organ toxicity - single exposure Category 3 (respiratory tract irritation), Acute Aquatic Hazard Category 3 | |
| Legend: | 1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI | |

Label elements

AMMONIUM METAVANADATE

Issue Date: **27/06/2017**Print Date: **20/06/2021**







| Signal word | Dang |
|-------------|------|
|-------------|------|

Hazard statement(s)

| H301 | Toxic if swallowed. |
|------|---------------------------------------|
| H330 | Fatal if inhaled. |
| H315 | Causes skin irritation. |
| H319 | Causes serious eye irritation. |
| H341 | Suspected of causing genetic defects. |
| H335 | May cause respiratory irritation. |
| H402 | Harmful to aquatic life. |

Precautionary statement(s) Prevention

| ,, | | |
|------|--|--|
| P201 | Obtain special instructions before use. | |
| P260 | Do not breathe dust/fume. | |
| P264 | Wash all exposed external body areas thoroughly after handling. | |
| P270 | Do not eat, drink or smoke when using this product. | |
| P271 | Use only outdoors or in a well-ventilated area. | |
| P280 | Wear protective gloves, protective clothing, eye protection and face protection. | |
| P273 | Avoid release to the environment. | |
| P284 | [In case of inadequate ventilation] wear respiratory protection. | |
| | | |

Precautionary statement(s) Response

| P301+P310 | IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician/first aider. | |
|----------------|--|--|
| P304+P340 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. | |
| P308+P313 | IF exposed or concerned: Get medical advice/ attention. | |
| P330 | Rinse mouth. | |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. | |
| P337+P313 | If eye irritation persists: Get medical advice/attention. | |
| P302+P352 | IF ON SKIN: Wash with plenty of water. | |
| P332+P313 | If skin irritation occurs: Get medical advice/attention. | |

Precautionary statement(s) Storage

| P403+P233 | Store in a well-ventilated place. Keep container tightly closed. | |
|-----------|--|--|
| P405 | Store locked up. | |

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

| CAS No | %[weight] | Name |
|-----------|-----------|-----------------------|
| 7803-55-6 | 100 | ammonium metavanadate |

Legend: 1. Classified by Cher

1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L;

* EU IOELVs available

Mixtures

See section above for composition of Substances

SECTION 4 First aid measures

Description of first aid measures

If this product comes in contact with the eyes:

Eye Contact

- ▶ Immediately hold eyelids apart and flush the eye continuously with running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
- Transport to hospital or doctor without delay.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

Chemwatch: 2859 Version No: 7.1.7.1 Page 3 of 10

AMMONIUM METAVANADATE

Issue Date: **27/06/2017**Print Date: **20/06/2021**

If skin contact occurs: Immediately remove all contaminated clothing, including footwear. **Skin Contact** Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation. ▶ If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Inhalation Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. ► Transport to hospital, or doctor, without delay. ► IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY. For advice, contact a Poisons Information Centre or a doctor. Urgent hospital treatment is likely to be needed In the mean time, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicated by the patient's condition. If the services of a medical officer or medical doctor are readily available, the patient should be placed in his/her care and a copy of the SDS should be provided. Further action will be the responsibility of the medical specialist If medical attention is not available on the worksite or surroundings send the patient to a hospital together with a copy of the SDS. Ingestion Where medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed otherwise INDUCE vomiting with fingers down the back of the throat, ONLY IF CONSCIOUS. Lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. NOTE: Wear a protective glove when inducing vomiting by mechanical means.

Indication of any immediate medical attention and special treatment needed

BAL has no apparent therapeutic benefit in vanadium poisoning but edetate calcium disodium and disodium catechol disulfonate are effective antidotes in animals.

BIOLOGICAL EXPOSURE INDEX - BEI

These represent the determinants observed in specimens collected from a healthy worker exposed at the Exposure Standard (ES or TLV):

 Determinant
 Sampling Time
 Index
 Comments

 Vanadium in urine
 End of shift at end of workweek
 50 ug/g creatinine
 SQ

SQ: Semi-quantitative determinant - interpretation may be ambiguous; should be used as a screening test or confirmatory test.

SECTION 5 Firefighting measures

Extinguishing media

- Water spray or fog.
- ► Foam
- ► Dry chemical powder.
- ► BCF (where regulations permit).
- Carbon dioxide.

Special hazards arising from the substrate or mixture

| Fire Incompatibility | None known. | |
|-------------------------|---|--|
| Advice for firefighters | | |
| Fire Fighting | Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water courses. Use fire fighting procedures suitable for surrounding area. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. Equipment should be thoroughly decontaminated after use. | |
| Fire/Explosion Hazard | ► Non combustible. ► Not considered a significant fire risk, however containers may burn. Decomposition may produce toxic fumes of: nitrogen oxides (NOx) metal oxides May emit poisonous fumes. | |
| HAZCHEM | 2Z | |

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills

▶ Clean up waste regularly and abnormal spills immediately.

Issue Date: 27/06/2017 Chemwatch: 2859 Page 4 of 10 Version No: 7.1.7.1 Print Date: 20/06/2021 AMMONIUM METAVANADATE

> Avoid breathing dust and contact with skin and eyes Wear protective clothing, gloves, safety glasses and dust respirator. Use dry clean up procedures and avoid generating dust. Vacuum up or sweep up. NOTE: Vacuum cleaner must be fitted with an exhaust micro filter (HEPA type) (consider explosion-proof machines designed to be grounded during storage and use). Dampen with water to prevent dusting before sweeping. Place in suitable containers for disposal. Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard.

Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water courses.

Major Spills No smoking, naked lights or ignition sources.

Increase ventilation. Stop leak if safe to do so.

Water spray or fog may be used to disperse / absorb vapour.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

- Avoid all personal contact, including inhalation.
 - Wear protective clothing when risk of exposure occurs.
 - Use in a well-ventilated area.
- Safe handling
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- ► DO NOT allow material to contact humans, exposed food or food utensils.
- Avoid contact with incompatible materials.
- ► When handling, **DO NOT** eat, drink or smoke.
- Other information
- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- ▶ Observe manufacturer's storage and handling recommendations contained within this SDS.

Conditions for safe storage, including any incompatibilities

- Lined metal can, lined metal pail/ can.
- Plastic pail.
- Polyliner drum.
- Packing as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

For low viscosity materials

- Drums and jerricans must be of the non-removable head type.
- ▶ Where a can is to be used as an inner package, the can must have a screwed enclosure.

For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.):

- Removable head packaging:
- Cans with friction closures and
- low pressure tubes and cartridges

Suitable container may be used.

> Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with inner and outer packages *

In addition, where inner packagings are glass and contain liquids of packing group I and II there must be sufficient inert absorbent to absorb any spillage *

unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.

All inner and sole packagings for substances that have been assigned to Packaging Groups I or II on the basis of inhalation toxicity criteria, must

Storage incompatibility

- WARNING: Avoid or control reaction with peroxides. All transition metal peroxides should be considered as potentially explosive. For example transition metal complexes of alkyl hydroperoxides may decompose explosively
- The pi-complexes formed between chromium(0), vanadium(0) and other transition metals (haloarene-metal complexes) and mono-or poly-fluorobenzene show extreme sensitivity to heat and are explosive.
- Avoid reaction with borohydrides or cyanoborohydrides
- ▶ Metals and their oxides or salts may react violently with chlorine trifluoride and bromine trifluoride.
- These trifluorides are hypergolic oxidisers. They ignite on contact (without external source of heat or ignition) with recognised fuels contact with these materials, following an ambient or slightly elevated temperature, is often violent and may produce ignition.
- ▶ The state of subdivision may affect the results.

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Not Available

Emergency Limits

| Energonoy Emilio | | | |
|-----------------------|------------|------------|----------|
| Ingredient | TEEL-1 | TEEL-2 | TEEL-3 |
| ammonium metavanadate | 0.01 mg/m3 | 0.11 mg/m3 | 80 mg/m3 |

Chemwatch: 2859 Version No: 7.1.7.1 Page 5 of 10

AMMONIUM METAVANADATE

Issue Date: **27/06/2017**Print Date: **20/06/2021**

| Ingredient | Original IDLH | Revised IDLH |
|-----------------------|---------------|---------------|
| ammonium metavanadate | Not Available | Not Available |

Occupational Exposure Banding

| Coodpariental Exposure Burlaining | | | | |
|-----------------------------------|--|----------------------------------|--|--|
| Ingredient | Occupational Exposure Band Rating | Occupational Exposure Band Limit | | |
| ammonium metavanadate | Е | ≤ 0.01 mg/m³ | | |
| Notes: | Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health. | | | |

Exposure controls

Appropriate engineering

controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.

Employers may need to use multiple types of controls to prevent employee overexposure.

Local exhaust ventilation usually required

Personal protection











- Safety glasses with side shields.
- Chemical goggles.

Eye and face protection

Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly.

Skin protection

See Hand protection below

- Wear chemical protective gloves, e.g. PVC.
- ▶ Wear safety footwear or safety gumboots, e.g. Rubber

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Hands/feet protection

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

Suitability and durability of glove type is dependent on usage.

Body protection

See Other protection below

Other protection

- Overalls.
- ► Eyewash unit.
- Barrier cream.
- ▶ Skin cleansing cream

Respiratory protection

Particulate. (AS/NZS 1716 & 1715, EN 143:2000 & 149:001, ANSI Z88 or national equivalent)

| Required Minimum Protection Factor | Half-Face Respirator | Full-Face Respirator | Powered Air Respirator |
|------------------------------------|----------------------|----------------------|------------------------|
| up to 10 x ES | P1 Air-line* | - | PAPR-P1 |
| up to 50 x ES | Air-line** | P2 | PAPR-P2 |
| up to 100 x ES | - | P3 | - |
| | | Air-line* | - |
| 100+ x ES | - | Air-line** | PAPR-P3 |

^{* -} Negative pressure demand ** - Continuous flow

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

AMMONIUM METAVANADATE

Issue Date: 27/06/2017 Print Date: 20/06/2021

- Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.
- The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).
- · Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.
- · Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.
- · Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU)
- Use approved positive flow mask if significant quantities of dust becomes airborne.
- · Try to avoid creating dust conditions.

SECTION 9 Physical and chemical properties

| Information | on basic | nhysical | and chemica | Inconecties |
|----------------|-----------|-----------|-------------|---------------|
| IIIIOIIIIauoii | UII Dasic | DIIVSICAL | and chemica | i bi obei des |

| Appearance | White odourless crystalline solid; mixes with water. Insoluble in saturated ammonium chloride solution. | | |
|--|---|---|----------------|
| | | | |
| Physical state | Divided Solid | Relative density (Water = 1) | 2.326 |
| Odour | Not Available | Partition coefficient n-octanol / water | Not Available |
| Odour threshold | Not Available | Auto-ignition temperature (°C) | Not Applicable |
| pH (as supplied) | Not Applicable | Decomposition temperature | Not Available |
| Melting point / freezing point (°C) | 690 | Viscosity (cSt) | Not Applicable |
| Initial boiling point and boiling range (°C) | 210 (decomposes) | Molecular weight (g/mol) | 116.99 |
| Flash point (°C) | Not Applicable | Taste | Not Available |
| Evaporation rate | Not Applicable | Explosive properties | Not Available |
| Flammability | Not Applicable | Oxidising properties | Not Available |
| Upper Explosive Limit (%) | Not Applicable | Surface Tension (dyn/cm or mN/m) | Not Applicable |
| Lower Explosive Limit (%) | Not Applicable | Volatile Component (%vol) | Not Applicable |
| Vapour pressure (kPa) | Not Applicable | Gas group | Not Available |
| Solubility in water | Miscible | pH as a solution (%) | Not Applicable |
| Vapour density (Air = 1) | Not Applicable | VOC g/L | Not Available |

SECTION 10 Stability and reactivity

| Reactivity | See section 7 |
|------------------------------------|--|
| Chemical stability | Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur. |
| Possibility of hazardous reactions | See section 7 |
| Conditions to avoid | See section 7 |
| Incompatible materials | See section 7 |
| Hazardous decomposition products | See section 5 |

SECTION 11 Toxicological information

Information on toxicological effects

| Inhaled | Inhalation of dusts, generated by the material, during the course of normal handling, may produce severely toxic effects; these may be fatal. The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled. If prior damage to the circulatory or nervous systems has occurred or if kidney damage has been sustained, proper screenings should be conducted on individuals who may be exposed to further risk if handling and use of the material result in excessive exposures. The inhalation of vanadium dust can cause irritation of the respiratory tract and eyes, with cough, wheezing, bronchitis, phlegm with blood stains, and blackening of the tongue. Internal symptoms may include loss of appetite, anaemia, nausea, headache, sleep difficulties, nervousness, dizziness, kidney damage, tremor, psychic disturbances and blindness. Inhalation of dusts, generated by the material during the course of normal handling, may produce serious damage to the health of the individual. |
|-----------|--|
| Ingestion | Toxic effects may result from the accidental ingestion of the material; animal experiments indicate that ingestion of less than 40 gram may be fatal or may produce serious damage to the health of the individual. Vanadium poisoning causes immediate distress with nose bleeds, severe diarrhoea, paralysis of the legs, breathing difficulties, convulsions and death. The liver and kidneys may degenerate, and sometimes there can be bleeding from the lung and adrenal cortex. Large doses of ammonia or injected ammonium salts may produce diarrhoea and may be sufficiently absorbed to produce increased production of urine and systemic poisoning. Symptoms include weakening of facial muscle, tremor, anxiety, reduced muscle and limb control. |

Chemwatch: 2859 Version No: 7.1.7.1

AMMONIUM METAVANADATE

Page 7 of 10

Issue Date: 27/06/2017 Print Date: 20/06/2021

This material can cause inflammation of the skin on contact in some persons. The material may accentuate any pre-existing dermatitis condition

Skin Contact Open cuts, abraded or irritated skin should not be exposed to this material

> Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

Eye

This material can cause eye irritation and damage in some persons.

Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems. Strong evidence exists that this substance may cause irreversible mutations (though not lethal) even following a single exposure Laboratory (in vitro) and animal studies show, exposure to the material may result in a possible risk of irreversible effects, with the possibility of producing mutation.

Chronic

Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. Long term exposure to high dust concentrations may cause changes in lung function i.e. pneumoconiosis, caused by particles less than 0.5 micron penetrating and remaining in the lung.

Vanadium is an essential trace element. Poisoning can cause stomach upset, emphysema and wheezing.

There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment.

ammonium metavanadate

| TOXICITY | IRRITATION |
|--|---------------|
| dermal (rat) LD50: >2500 mg/kg ^[1] | Not Available |
| Inhalation(Rat) LC50; 2.43 mg/l4h ^[1] | |
| Oral(Rat) LD50; 141.4 mg/kg ^[1] | |

Legend:

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

AMMONIUM METAVANADATE

Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production.

| Acute Toxicity | ✓ | Carcinogenicity | × |
|-----------------------------------|----------|--------------------------|---|
| Skin Irritation/Corrosion | ✓ | Reproductivity | × |
| Serious Eye Damage/Irritation | ✓ | STOT - Single Exposure | ✓ |
| Respiratory or Skin sensitisation | × | STOT - Repeated Exposure | × |
| Mutagenicity | ✓ | Aspiration Hazard | × |

Legend:

X - Data either not available or does not fill the criteria for classification

Data available to make classification

SECTION 12 Ecological information

Toxicity

| ammonium metavanadate | Endpoint NOEC(ECx) | Test Duration (hr) 6h | Species Fish | Value 116.99mg/L | Source 4 |
|-----------------------|---|-----------------------|-----------------|---------------------|-------------|
| Legend: | Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data | | | | |

Harmful to aquatic organisms.

For Vanadium Compounds:

Environmental Fate: Vanadium is travels through the environment via long-range transportation in the atmosphere, water, and land by natural and man-made sources, wet and dry deposition, adsorption and complexing. From natural sources, vanadium is probably in the form of less soluble trivalent mineral particles.

Atmospheric Fate: Vanadium generally enters the atmosphere as an aerosol. Natural and man-made sources of vanadium tend to release large particles that are more likely to settle near the source. Smaller particles, such as those emitted from oil-fueled power plants, have a longer residence time in the atmosphere and are more likely to be transported farther away from the site of release.

Terrestrial Fate: Soil - Transport and partitioning of vanadium in soil is influenced by pH and reduction potential. Ferric hydroxides and solid bitumens (organic) are the main carriers of vanadium in the sedimentation process. Iron acts as a carrier for trivalent vanadium and is responsible for its diffusion through molten rocks where it becomes trapped during crystallization.

For Ammonia:

Atmospheric Fate: Ammonia reacts rapidly with available acids (mainly sulfuric, nitric, and sometimes hydrochloric acid) to form the corresponding salts. Ammonia is persistent in the

Aquatic Fate: Biodegrades rapidly to nitrate, producing a high oxygen demand. Non-persistent in water (half-life 2 days).

Ecotoxicity: Moderately toxic to fish under normal temperature and pH conditions and harmful to aquatic life at low concentrations. Does not concentrate in food chain. DO NOT discharge into sewer or waterways

Persistence and degradability

| Ingredient | Persistence: Water/Soil | Persistence: Air |
|-----------------------|-------------------------|------------------|
| ammonium metavanadate | HIGH | HIGH |

Bioaccumulative potential

Page 8 of 10

AMMONIUM METAVANADATE

Issue Date: 27/06/2017 Print Date: 20/06/2021

| Ingredient | Bioaccumulation | |
|-----------------------|----------------------|--|
| ammonium metavanadate | LOW (LogKOW = 2.229) | |
| Mobility in soil | | |

| Ingredient | Mobility |
|-----------------------|-------------------|
| ammonium metavanadate | LOW (KOC = 35.04) |

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal

- ▶ Containers may still present a chemical hazard/ danger when empty.
- Return to supplier for reuse/ recycling if possible.

Otherwise:

- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
- ▶ Where possible retain label warnings and SDS and observe all notices pertaining to the product.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- ▶ Reduction
- ► Reuse
- Recycling
 - Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate. In most instances the supplier of the material should be consulted.

- DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- ▶ Where in doubt contact the responsible authority.
- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Management Authority for disposal.
- Bury residue in an authorised landfill.
- Recycle containers if possible, or dispose of in an authorised landfill.

SECTION 14 Transport information

Labels Required



| Marine Pollutant | NC |
|------------------|----|
| HAZCHEM | 27 |

Land transport (ADG)

| UN number | 2859 | | |
|------------------------------|--|--|--|
| UN proper shipping name | AMMONIUM METAVANADATE | | |
| Transport hazard class(es) | Class 6.1 Subrisk Not Applicable | | |
| Packing group | II | | |
| Environmental hazard | Not Applicable | | |
| Special precautions for user | Special provisions Not Applicable Limited quantity 500 g | | |

Air transport (ICAO-IATA / DGR)

| UN number | 2859 | | | |
|----------------------------|--|---------------------------|--|--|
| UN proper shipping name | Ammonium metavanadate | | | |
| Transport hazard class(es) | ICAO/IATA Class ICAO / IATA Subrisk ERG Code | .1 lot Applicable L | | |
| Packing group | II | | | |
| Environmental hazard | Not Applicable | | | |

Page 9 of 10

AMMONIUM METAVANADATE

Issue Date: **27/06/2017**Print Date: **20/06/2021**

| | Special provisions | Not Applicable |
|------------------------------|---|----------------|
| | Cargo Only Packing Instructions | 676 |
| | Cargo Only Maximum Qty / Pack | 100 kg |
| Special precautions for user | Passenger and Cargo Packing Instructions | 669 |
| | Passenger and Cargo Maximum Qty / Pack | 25 kg |
| | Passenger and Cargo Limited Quantity Packing Instructions | Y644 |
| | Passenger and Cargo Limited Maximum Qty / Pack | 1 kg |

Sea transport (IMDG-Code / GGVSee)

| UN number | 2859 | | | |
|------------------------------|---|-----------------------|--|--|
| UN proper shipping name | AMMONIUM METAVA | AMMONIUM METAVANADATE | | |
| Transport hazard class(es) | | | | |
| Packing group | | | | |
| Environmental hazard | Not Applicable | | | |
| Special precautions for user | EMS Number F-A , S-A Special provisions Not Applicable Limited Quantities 500 g | | | |

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

| Product name | Group |
|-----------------------|---------------|
| ammonium metavanadate | Not Available |

Transport in bulk in accordance with the ICG Code

| Product name | Ship Type |
|-----------------------|---------------|
| ammonium metavanadate | Not Available |

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

ammonium metavanadate is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

Chemical Footprint Project - Chemicals of High Concern List

National Inventory Status

| National Inventory | Status | |
|--|---|--|
| Australia - AIIC / Australia Non-Industrial Use | Yes | |
| Canada - DSL | Yes | |
| Canada - NDSL | No (ammonium metavanadate) | |
| China - IECSC | Yes | |
| Europe - EINEC / ELINCS / NLP | Yes | |
| Japan - ENCS | Yes | |
| Korea - KECI | Yes | |
| New Zealand - NZIoC | Yes | |
| Philippines - PICCS | Yes | |
| USA - TSCA | Yes | |
| Taiwan - TCSI | Yes | |
| Mexico - INSQ | Yes | |
| Vietnam - NCI | Yes | |
| Russia - FBEPH | Yes | |
| Legend: | Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets) | |

SECTION 16 Other information

| Revision Date | 27/06/2017 |
|---------------|---------------|
| Initial Date | Not Available |

Chemwatch: 2859 Page 10 of 10 Version No: 7.1.7.1

AMMONIUM METAVANADATE

Issue Date: 27/06/2017 Print Date: 20/06/2021

SDS Version Summary

| Version | Date of Update | Sections Updated |
|---------|-------------------|--|
| 6.1.1.1 | 13/11/2009 | Acute Health (eye), Acute Health (inhaled), Acute Health (skin), Chronic Health, Classification, Disposal, Environmental, First Aid (skin), Personal Protection (eye), Spills (minor), Supplier Information, Toxicity and Irritation (Other) |
| 6.1.2.1 | 26/04/2021 | Regulation Change |
| 6.1.3.1 | 03/05/2021 | Regulation Change |
| 6.1.4.1 | 06/05/2021 | Regulation Change |
| 6.1.5.1 | 10/05/2021 | Regulation Change |
| 6.1.5.2 | 30/05/2021 | Template Change |
| 6.1.5.3 | 04/06/2021 | Template Change |
| 6.1.5.4 | 05/06/2021 | Template Change |
| 6.1.6.4 | 07/06/2021 | Regulation Change |
| 6.1.6.5 | 09/06/2021 | Template Change |
| 6.1.6.6 | 11/06/2021 | Template Change |
| 6.1.6.7 | 15/06/2021 | Template Change |
| 6.1.7.7 | 17/06/2021 | Regulation Change |

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit $_{\circ}$

IDLH: Immediately Dangerous to Life or Health Concentrations

ES: Exposure Standard OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index

AIIC: Australian Inventory of Industrial Chemicals

DSL: Domestic Substances List

NDSL: Non-Domestic Substances List

IECSC: Inventory of Existing Chemical Substance in China

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

NLP: No-Longer Polymers

ENCS: Existing and New Chemical Substances Inventory

KECI: Korea Existing Chemicals Inventory

NZIoC: New Zealand Inventory of Chemicals

PICCS: Philippine Inventory of Chemicals and Chemical Substances

TSCA: Toxic Substances Control Act

TCSI: Taiwan Chemical Substance Inventory

INSQ: Inventario Nacional de Sustancias Químicas

NCI: National Chemical Inventory

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.