

ALPHA CHEMICALS PTY LTD

Chemwatch: 11379

Version No: 5.1

Safety Data Sheet according to WHS Regulations (Hazardous Chemicals) Amendment 2020 and ADG requirements

Chemwatch Hazard Alert Code: 3

Issue Date: 20/06/2022 Print Date: 14/07/2022 S.GHS.AUS.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

| Product name | BARIUM CHLORIDE, DIHYDRATE | |
|-------------------------------|---|--|
| Chemical Name | barium chloride, dihydrate | |
| Synonyms | BaCl2.2H2O; barium dichloride hydrated; barium dichloride dihydrate; Jasol barium chloride dihydrate; barium chloride, UNILAB, UNIVAR; Product Code: 10047-17006-27290; Barium Chloride Dihydrate GR ACS ISO | |
| Proper shipping name | BARIUM COMPOUND, N.O.S. (contains barium chloride, dihydrate) | |
| Chemical formula | BaCl2-2H2O Ba-Cl2 | |
| Other means of identification | Not Available | |
| CAS number | 10326-27-9 | |

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Manufacture of pigments, colour lakes, glass, mordant for acid dyes; weighting and dyeing textile fabrics; in aluminium refining; as a pesticide; boiler compounds for softening water; tanning and finishing leather.

Details of the supplier of the safety data sheet

| Registered company name | ALPHA CHEMICALS PTY LTD | |
|-------------------------|---|--|
| Address | ALLEN PLACE WETHERILL PARK NSW 2099 Australia | |
| Telephone | (0)2 9982 4622 | |
| Fax | Not Available | |
| Website | ~ | |
| Email | shane@alphachem.com.au | |

Emergency telephone number

| Association / Organisation | ALPHA CHEMICALS PTY LTD | CHEMWATCH EMERGENCY RESPONSE | |
|-----------------------------------|-------------------------|------------------------------|--|
| Emergency telephone numbers | 61 (0)418 237 771 | +61 1800 951 288 | |
| Other emergency telephone numbers | Not Available | +61 3 9573 3188 | |

Once connected and if the message is not in your prefered language then please dial 01

SECTION 2 Hazards identification

Classification of the substance or mixture

HAZARDOUS CHEMICAL. DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

ChemWatch Hazard Ratings

| | Min | Max | |
|--------------|-----|-----|---|
| Flammability | 0 | | |
| Toxicity | 3 | | 0 = Minimum |
| Body Contact | 1 📃 | 1 | 1 = Low |
| Reactivity | 0 | | 2 = Moderate 3 = High 4 = Extreme |
| Chronic | 0 | 1 | |

| Poisons Schedule | S6 | |
|-------------------------------|--|--|
| Classification ^[1] | Acute Toxicity (Oral) Category 3, Acute Toxicity (Inhalation) Category 4 | |
| Legend: | 1. Classified by Chernwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI | |

| Hazard pictogram(s) | | |
|---------------------|---------------------|--|
| | | |
| Signal word | Danger | |
| | | |
| Hazard statement(s) | | |
| H301 | Toxic if swallowed. | |

Precautionary statement(s) Prevention

H332

| • • • • • | |
|--|---|
| P264 Wash all exposed external body areas thoroughly after handling. | |
| P270 | Do not eat, drink or smoke when using this product. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P261 | Avoid breathing dust/fumes. |

Precautionary statement(s) Response

| P301+P310 | IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician/first aider. | |
|-----------|--|--|
| P330 | Rinse mouth. | |
| P312 | Call a POISON CENTER/doctor/physician/first aider/if you feel unwell. | |
| P304+P340 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. | |

Precautionary statement(s) Storage

P405 Store locked up.

Harmful if inhaled.

Precautionary statement(s) Disposal

Not Applicable

SECTION 3 Composition / information on ingredients

P501

Substances

| CAS No | | %[weight] | Name |
|------------|---|-----------|----------------------------|
| 10326-27-9 | | >99 | barium chloride, dihydrate |
| Legend: | 1: Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L, * EU IOELVs available | | |

Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

Mixtures

See section above for composition of Substances

SECTION 4 First aid measures

Description of first aid measures

| Eye Contact | If this product comes in contact with the eyes: Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. | |
|--------------|--|--|
| Skin Contact | If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation. | |
| Inhalation | If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor. | |
| Ingestion | IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY. For advice, contact a Poisons Information Centre or a doctor. Urgent hospital treatment is likely to be needed. In the mean time, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicated by the patient's condition. If the services of a medical officer or medical doctor are readily available, the patient should be placed in his/her care and a copy of the SDS should be provided. Further action will be the responsibility of the medical specialist. If medical attention is not available on the worksite or surroundings send the patient to a hospital together with a copy of the SDS. | |

Where medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed otherwise: • INDUCE vomiting with fingers down the back of the throat, ONLY IF CONSCIOUS. Lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration NOTE: Wear a protective glove when inducing vomiting by mechanical means. Indication of any immediate medical attention and special treatment needed

Acute barium poisoning gives a rapid decrease in blood potassium level. Administration of appropriate potassium salts has been recommended. [Genium]

- + After ingestion of barium acid salts, severe gastro-intestinal irritation followed by muscle twitching, progressive flaccid paralysis and severe hypokalaemia and hypertension, occurs
- ▶ Respiratory failure, renal failure and occasional cardiac dysrhythmias may result from an acute ingestion.
- Use sodium sulfate as a cathartic. Add 5-10 gm of sodium sulfate to lavage solution or as fluid supplement to lpecac syrup (the sulfate salt is not absorbed)
- Monitor cardiac rhythm and serum potassium closely to establish the trend over the first 24 hours. Large doses of potassium may be needed to correct the hypokalaemia. ٠
- Administer generous amounts of fluid replacement but monitor the urine and serum for evidence of renal failure. [Ellenhorn and Barceloux: Medical Toxicology]

SECTION 5 Firefighting measures

Extinguishing media

- Water spray or fog.
- Foam.
- Dry chemical powder.
- BCF (where regulations permit). ÷
- Carbon dioxide.

Special betards arising from the substrate or mixture

| Special hazards arising from the substrate or mixture | | | |
|---|---|--|--|
| Fire Incompatibility | None known. | | |
| Advice for firefighters | | | |
| Fire Fighting | Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water courses. Use fire fighting procedures suitable for surrounding area. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. Equipment should be thoroughly decontaminated after use. | | |
| Fire/Explosion Hazard | Non combustible. Not considered a significant fire risk, however containers may burn. Decomposition may produce toxic fumes of: hydrogen chloride metal oxides Decomposes at high temperatures to produce barium oxide. Barium oxide is strongly alkaline and, upon contact with water, is exothermic. When barium oxide reacts with oxygen to give a peroxide, there is a fire and explosion risk. May emit poisonous fumes. | | |
| HAZCHEM | 2Z | | |

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

| Minor Spills | Remove all ignition sources. Clean up all spills immediately. Avoid contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Use dry clean up procedures and avoid generating dust. Place in a suitable, labelled container for waste disposal. |
|--------------|---|
| Major Spills | Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water courses. No smoking, naked lights or ignition sources. Increase ventilation. Stop leak if safe to do so. Water spray or fog may be used to disperse / absorb vapour. |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling

Avoid all personal contact, including inhalation.

Continued...

| | Use in a well-ventilated area. Prevent concentration in hollows and sumps. DO NOT enter confined spaces until atmosphere has been checked. DO NOT allow material to contact humans, exposed food or food utensils. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Store in original containers. |
|-------------------|--|
| Other information | Keep containers securely sealed. Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this SDS. |

Conditions for safe storage, including any incompatibilities

| · · · · · · · · · · · · · · · · · · · | ······································ |
|---------------------------------------|--|
| Suitable container | Glass container is suitable for laboratory quantities Lined metal can, lined metal pail/ can. Plastic pail. Polyliner drum. Packing as recommended by manufacturer. Check all containers are clearly labelled and free from leaks. For low viscosity materials Drums and jerricans must be of the non-removable head type. Where a can is to be used as an inner package, the can must have a screwed enclosure. For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.): Removable head packaging; Cans with friction closures and low pressure tubes and cartridges may be used. Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with inner and outer packages *. In addition, where inner packagings are glass and contain liquids of packing group I and II there must be sufficient inert absorbent to absorb any spillage *. wiless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic. |
| Storage incompatibility | Avoid reaction with 2-furan percarboxylic acid. Metals and their oxides or salts may react violently with chlorine trifluoride and bromine trifluoride. These trifluorides are hypergolic oxidisers. They ignite on contact (without external source of heat or ignition) with recognised fuels - contact with these materials, following an ambient or slightly elevated temperature, is often violent and may produce ignition. The state of subdivision may affect the results. Avoid strong acids, acid chlorides, acid anhydrides and chloroformates. Avoid reaction with oxidising agents |

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

| Source | Ingredient | Material na | me | TWA | STEL | Peak | Notes |
|------------------------------|----------------------------|--------------|------------------------|--------------|---------------|---------------|---------------|
| Australia Exposure Standards | barium chloride, dihydrate | Barium, solu | ible compounds (as Ba) | 0.5 mg/m3 | Not Available | Not Available | Not Available |
| Emergency Limits | | | | | | | |
| Ingredient | TEEL-1 | | TEEL-2 | | TEEL-3 | | |
| barium chloride, dihydrate | 2.7 mg/m3 | | 330 mg/m3 | | 2,000 mg/m3 | | |
| barium chloride, dihydrate | 2.3 mg/m3 | | 280 mg/m3 | | 1,700 mg/m3 | | |
| Ingredient | Original IDLH | | | Revised IDLH | | | |
| barium chloride, dihydrate | 50 mg/m3 | | Not Available | | | | |

Exposure controls

| Appropriate engineering controls | Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure. Local exhaust ventilation usually required. |
|-------------------------------------|--|
| Personal protection | |

| Eye and face protection | Safety glasses with side shields. Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. |
|-------------------------|--|
| Skin protection | See Hand protection below |
| Hands/feet protection | Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended. Suitability and durability of glove type is dependent on usage. |
| Body protection | See Other protection below |
| Other protection | Overalls. Eyewash unit. Barrier cream. Skin cleansing cream. |

Respiratory protection

Particulate. (AS/NZS 1716 & 1715, EN 143:2000 & 149:001, ANSI Z88 or national equivalent)

| Required Minimum Protection Factor | Half-Face Respirator | Full-Face Respirator | Powered Air Respirator |
|------------------------------------|----------------------|----------------------|------------------------|
| up to 10 x ES | P1 Air-line* | - | PAPR-P1 - |
| up to 50 x ES | Air-line** | P2 | PAPR-P2 |
| up to 100 x ES | - | P3 | - |
| | | Air-line* | - |
| 100+ x ES | - | Air-line** | PAPR-P3 |

* - Negative pressure demand ** - Continuous flow

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

· Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.

• The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).

Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.

Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.
 Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU)

Use approved positive flow mask if significant quantities of dust becomes airborne.

Try to avoid creating dust conditions.

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

| Appearance | Colourless, odourless, monoclinic crystals, with a bitter, salty taste. Soluble in water, methanol. Almost soluble in ethanol, acetone, ethyl acetate. Loses water of hydration @ 113 deg.C. to become anhydrous form, which melts @ 963 deg.C. | | | |
|---|---|---|----------------|--|
| Physical state | Divided Solid | Relative density (Water = 1) | 3.86 @ 24C | |
| Odour | Not Available | Partition coefficient n-octanol / water | Not Available | |
| Odour threshold | Not Available | Auto-ignition temperature (°C) | Not Applicable | |
| pH (as supplied) | Not Applicable | Decomposition temperature (°C) | Not Available | |
| Melting point / freezing point (°C) | 963 (anhydrous) | Viscosity (cSt) | Not Applicable | |
| Initial boiling point and boiling range (°C) | 1560 (anhydrous) | Molecular weight (g/mol) | 244.28 | |
| Flash point (°C) | Not Applicable | Taste | Not Available | |
| Evaporation rate | Not Applicable | Explosive properties | Not Available | |
| Flammability | Not Applicable | Oxidising properties | Not Available | |
| Upper Explosive Limit (%) | Not Applicable | Surface Tension (dyn/cm or mN/m) | Not Applicable | |
| Lower Explosive Limit (%) | Not Applicable | Volatile Component (%vol) | Not Applicable | |

| Vapour pressure (kPa) | Not Applicable | Gas group | Not Available |
|--------------------------|----------------|--------------------------------------|---------------|
| Solubility in water | Miscible | pH as a solution (Not Available%) | Not Available |
| Vapour density (Air = 1) | Not Applicable | VOC g/L | Not Available |

SECTION 10 Stability and reactivity

| Reactivity | See section 7 |
|-------------------------------------|--|
| Chemical stability | Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur. |
| Possibility of hazardous reactions | See section 7 |
| Conditions to avoid | See section 7 |
| Incompatible materials | See section 7 |
| Hazardous decomposition products | See section 5 |

SECTION 11 Toxicological information

| Information on toxicological e | ffects | | | |
|--------------------------------|---|--|--|--|
| Inhaled | Inhalation of dusts, generated by the material, during the course of normal handling, may be harmful. There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled. If prior damage to the circulatory or nervous systems has occurred or if kidney damage has been sustained, proper screenings should be conducted on individuals who may be exposed to further risk if handling and use of the material result in excessive exposures. Barium fumes are respiratory irritants. Over-exposure to barium dusts and fume may result in rhinitis, frontal headache, wheezing, laryngeal spasm, salivation and anorexia. Long term effects include nervous disorders and adverse effects on the heart, circulatory system and musculature. Heavy exposures may result in a benign pneumoconiosis. | | | |
| Ingestion | Acute effects of ingestion include abdominal pain, vomiting, diarrhoea, convulsions, muscular spasms and haemorrhage of the stomach, intestines and kidneys. Lethal dose may be as little as 1 gm. In test animals, acute doses have impaired the function of male and female reproductive organs. Toxic effects may result from the accidental ingestion of the material; animal experiments indicate that ingestion of less than 40 gram may be fatal or may produce serious damage to the health of the individual. Ingestion of soluble barium compounds may result in ulceration of the mucous membranes of the gastrointestinal tract, tightness in the muscles of the face and neck, gastroenteritis, vomiting, diarrhoea, muscular tremors and paralysis, anxiety, weakness, laboured breathing, cardiac irregularity due to contractions of smooth striated and cardiac muscles (often violent and painful), slow irregular pulse, hypertension, convulsions and respiratory failure. | | | |
| Skin Contact | The material is not thought to be a skin irritant (as classified by EC Directives using animal models). Abrasive damage however, may result from prolonged exposures. Skin contact with the material may damage the health of the individual; systemic effects may result following absorption. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. | | | |
| Eye | Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may cause transient discomfort characterised by tearing or conjunctival redness (as with windburn). Slight abrasive damage may also result. | | | |
| Chronic | Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. Long term exposure to high dust concentrations may cause changes in lung function i.e. pneumoconiosis, caused by particles less than 0.5 micron penetrating and remaining in the lung. Barium compounds may cause high blood pressure, airway irritation and damage the liver, spleen and bone marrow. Prolonged exposure may cause a lung inflammation and scarring. | | | |
| | ΤΟΧΙΟΙΤΥ | IRRITATION | | |
| barium chloride, dihydrate | dermal (rat) LD50: >2000 mg/kg ^[1] | Eye: adverse effect observed (irritating) ^[1] | | |
| | Oral (Guinea) LD50; 76 mg/kg ^[2] | Skin: no adverse effect observed (not irritating) ^[1] | | |
| Legend: | Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances | | | |
| | | | | |
| BARIUM CHLORIDE, | Oral (rat) TDLo: 16000 mg/kg/13W-C Nil reported | | | |

| DIHYDRATE | Oral (rat) TDLo: 16000 mg/kg/13W-C Nil reported | | |
|--------------------------------------|---|--------------------------|---|
| | | | |
| Acute Toxicity | × | Carcinogenicity | × |
| Skin Irritation/Corrosion | × | Reproductivity | × |
| Serious Eye Damage/Irritation | × | STOT - Single Exposure | × |
| Respiratory or Skin sensitisation | × | STOT - Repeated Exposure | × |
| Mutagenicity | × | Aspiration Hazard | × |

SECTION 12 Ecological information

| 「oxicity | | | | | |
|------------------------------|----------------|---|-------------------------------|---------|--------|
| London at Lord to 1915, have | Endpoint | Test Duration (hr) | Species | Value | Source |
| barium chloride, dihydrate | EC10(ECx) | 24h | Algae or other aquatic plants | 240mg/l | 4 |
| Legend: | Ecotox databas | 1. IUCLID Toxicity Data 2. Europe ECHA Registered le - Aquatic Toxicity Data 5. ECETOC Aquatic Haza ion Data 8. Vendor Data | • | | |

For Chloride: Although inorganic chloride ions are not normally considered toxic they can exist in effluents at acutely toxic levels. Incidental exposure to inorganic chloride may occur in occupational settings where chemicals management policies are improperly applied. The toxicity of chloride salts depends on the counter-ion (cation) present; that of chloride itself is unknown. Chloride toxicity has not been observed in humans except in the special case of impaired sodium chloride metabolism, e.g. in congestive heart failure. Healthy individuals can tolerate the intake of large quantities of chloride that there is an intake of fresh water following ingestion. Although excessive intake of drinking-water containing sodium chloride at solve 2.5 g/L has been reported to produce hypertension, this effect is believed to be related to the sodium ion concentration. Chloride concentrations in excess of about 250 mg/L can give rise to detectable taste in water. Consumers can, however, become accustomed to concentrations in excess of 250 mg/L. For Barium and its Compounds:

Environmental Fate: Barium is a highly reactive metal occurring naturally only in a combined state, primarily as inorganic complexes. Conditions such as pH, oxidation-reduction potential, cation exchange capacity, and the presence of sulfate, carbonate, and the presence of metal oxides will affect the partitioning of barium and its compounds in the environment. The element is released to environmental by both natural processes and man-made sources. Most barium released to the environment from industrial sources is in forms that do not become widely dispersed.

Atmospheric Fate: In the atmosphere, barium is likely to be present in particulate form. Barium compounds will be removed from the atmosphere via wet/dry deposition. The substance may change to different forms of barium in the air.

Terrestrial Fate: Soil - Barium will leach from geological formations to groundwater and will adsorb to soil.

DO NOT discharge into sewer or waterways.

Persistence and degradability

| Persistence: Water/Soil | Persistence: Air |
|-------------------------|--|
| HIGH | HIGH |
| | |
| | |
| Bioaccumulation | |
| LOW (BCF = 60) | |
| | |
| | |
| Mobility | |
| LOW (KOC = 23.74) | |
| | HIGH Bioaccumulation LOW (BCF = 60) Mobility |

SECTION 13 Disposal considerations

| Product / Packaging disposal | Containers may still present a chemical hazard/ danger when empty. Return to supplier for reuse/ recycling if possible. Otherwise: If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. Where possible retain label warnings and SDS and observe all notices pertaining to the product. Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked. A Hierarchy of Controls seems to be common - the user should investigate: Reduction Reuse Recycling Disposal (if all else fails) This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate. In most instances the supplier of the material should be consulted. DO NOT allow wash water from cleaning or process equipment to enter drains. It may be necessary to collect all wash water for treatment before disposal. In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. Where in doubt contact the responsible authority. Recycle wherever possible or consult manufacturer for recycling options. Consult State Land Waste Management Authority for disposal. Bury residue in an authorised landfill. Recycle containers if possible, or dispose of in an authorised landfill. |
|------------------------------|--|
|------------------------------|--|

SECTION 14 Transport information

Labels Required

| Labels Required | |
|------------------|----|
| | 6 |
| Marine Pollutant | NO |

HAZCHEM 2Z

| Land transport (ADG) | | | |
|------------------------------|---|--|--|
| UN number | 1564 | | |
| UN proper shipping name | BARIUM COMPOUND, N.O.S. (contains barium chloride, dihydrate) | | |
| Transport hazard class(es) | Class 6.1 Subrisk Not Applicable | | |
| Packing group | III | | |
| Environmental hazard | Not Applicable | | |
| Special precautions for user | Special provisions177 223 274Limited quantity5 kg | | |

Air transport (ICAO-IATA / DGR)

| UN number | 1564 | | |
|------------------------------|---|----------------------------|--------|
| UN proper shipping name | Barium compound, n.o.s. * (contains barium chloride, dihydrate) | | |
| | ICAO/IATA Class | 6.1 | |
| Transport hazard class(es) | ICAO / IATA Subrisk | Not Applicable | |
| | ERG Code | 6L | |
| Packing group | III | | |
| Environmental hazard | Not Applicable | | |
| | Special provisions | | A3 A82 |
| | Cargo Only Packing Instructions | | 677 |
| | Cargo Only Maximum Qty / Pack | | 200 kg |
| Special precautions for user | Passenger and Cargo Packing Instructions | | 670 |
| | Passenger and Cargo | 100 kg | |
| | Passenger and Cargo Limited Quantity Packing Instructions | | Y645 |
| | Passenger and Cargo | Limited Maximum Qty / Pack | 10 kg |

Sea transport (IMDG-Code / GGVSee)

| UN number | 1564 | | | |
|------------------------------|--|---|--|--|
| UN proper shipping name | BARIUM COMPOUN | BARIUM COMPOUND, N.O.S. (contains barium chloride, dihydrate) | | |
| Transport hazard class(es) | | 6.1 Not Applicable | | |
| Packing group | III | | | |
| Environmental hazard | Not Applicable | | | |
| Special precautions for user | EMS Number Special provisions Limited Quantities | | | |

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

| Product name | Group |
|----------------------------|---------------|
| barium chloride, dihydrate | Not Available |

Transport in bulk in accordance with the ICG Code

| Product name | Ship Type |
|----------------------------|---------------|
| barium chloride, dihydrate | Not Available |

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

barium chloride, dihydrate is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -Schedule 6 Australian Inventory of Industrial Chemicals (AIIC)

National Inventory Status

| National Inventory | Status |
|--|---|
| Australia - AIIC / Australia Non-Industrial Use | Yes |
| Canada - DSL | Yes |
| Canada - NDSL | No (barium chloride, dihydrate) |
| China - IECSC | Yes |
| Europe - EINEC / ELINCS / NLP | Yes |
| Japan - ENCS | No (barium chloride, dihydrate) |
| Korea - KECI | Yes |
| New Zealand - NZIoC | Yes |
| Philippines - PICCS | Yes |
| USA - TSCA | Yes |
| Taiwan - TCSI | Yes |
| Mexico - INSQ | Yes |
| Vietnam - NCI | Yes |
| Russia - FBEPH | Yes |
| Legend: | Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration. |

SECTION 16 Other information

| Revision Date | 20/06/2022 |
|---------------|------------|
| Initial Date | 05/04/2005 |

SDS Version Summary

| Version | Date of Update | Sections Updated |
|---------|----------------|-------------------------------|
| 5.1 | 20/06/2022 | Expiration. Review and Update |

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average PC-STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit。 IDLH: Immediately Dangerous to Life or Health Concentrations ES: Exposure Standard OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors **BEI: Biological Exposure Index** AIIC: Australian Inventory of Industrial Chemicals DSL: Domestic Substances List NDSL: Non-Domestic Substances List IECSC: Inventory of Existing Chemical Substance in China EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European List of Notified Chemical Substances NLP: No-Longer Polymers ENCS: Existing and New Chemical Substances Inventory KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals PICCS: Philippine Inventory of Chemicals and Chemical Substances TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas NCI: National Chemical Inventory FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.