

SODIUM SULPHITE ALPHA CHEMICALS PTY LTD

Chemwatch: 21891

Chemwatch Hazard Alert Code: 2

Issue Date: **23/12/2022** Print Date: **24/01/2024** S.GHS.AUS.EN

Version No: **8.1**Safety Data Sheet according to WHS Regulations (Hazardous Chemicals) Amendment 2020 and ADG requirements

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier		
Product name	SODIUM SULPHITE	
Chemical Name	Not Available	
Synonyms	Na2-SO3; sodium sulphite; anhydrous sodium sulphite; anhydrous sodium sulfite; disodium sulphite; disodium sulfite; exiccated sodium sulphite; exiccated sodium sulfite; Sulftech; sulphurous acid, sodium salt (1:2); sulfurous acid, sodium salt (1:2); sodium sulphite hydrated; sodium sulfite hydrated; sodium sulphite heptahydrate; disodium sulphite heptahydrate; disodium sulfite heptahydrate; AR0000509 PHOT00005917 TECH00004252 UL00000512; BTW 2010; BTW2010; BTW-2010; sodium sulfite; sodium sulfite anhydrous AnalaR, 10357; sodium sulphite anhydrous	
Chemical formula	O3S-2Na-7H2O O3-S.2Na H2O3S.2Na	
Other means of identification	Not Available	
CAS number	7757-83-7	

Relevant identified uses of the substance or mixture and uses advised against

Used chiefly in photographic developers and instead of 'hypo' for fixing prints; bleaching wool, straw, silk; generating sulphur dioxides; as reducer in the manufacture of dyes; silvering glass. Also used for removing traces of chlorine in bleached textiles and paper; preserving meat and egg yolks. [~Intermediate ~]
Reducing agent

Relevant identified uses

Inorganic sulfites, bisulfites and metabisulfites (sodium, potassium and ammonium salts) are defined as substances that liberate sulphur dioxide under certain conditions. Therefore the officially tabled limits for these chemicals normally correspond to the yield of deliberated sulfur dioxide. Due to the fact that bisulfites do not exist as solids, an aqueous solution of about 40% represents the maximum concentration of this chemical. Therefore a bisulfite solution will become a solid metabisulfite after removal of water vice versa. The conversion of sulphur dioxide to bisulfite and sulfite is strongly pH dependent in aqueous solutions.

Details of the manufacturer or supplier of the safety data sheet

Registered company name	ALPHA CHEMICALS PTY LTD
Address	4 ALLEN PLACE WETHERILL PARK NSW 2164 Australia
Telephone	61 (0)2 9982 4622
Fax	Not Available
Website	~
Email	shane@alphachem.com.au

Emergency telephone number

Association / Organisation	ALPHA CHEMICALS PTY LTD	CHEMWATCH EMERGENCY RESPONSE (24/7)
Emergency telephone numbers	61 (0)418 237 771	+61 1800 951 288
Other emergency telephone numbers	NOT AVAIIANIE	+61 3 9573 3188

Once connected and if the message is not in your preferred language then please dial 01

SECTION 2 Hazards identification

Classification of the substance or mixture

HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

Chemwatch Hazard Ratings

	Min M	lax
Flammability	0	!
Toxicity	2	0 = Minimum
Body Contact	2	1 = Low
Reactivity	1	2 = Moderate
Chronic	2	3 = High 4 = Extreme

SODIUM SULPHITE

Issue Date: 23/12/2022 Print Date: 24/01/2024

Poisons Schedule	Not Applicable
Classification ^[1]	Acute Toxicity (Oral) Category 4, Skin Corrosion/Irritation Category 2, Serious Eye Damage/Eye Irritation Category 2A, Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, Germ Cell Mutagenicity Category 2
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

Label elements

Hazard pictogram(s)





Signal word	Warnin

Hazard statement(s)

H302	Harmful if swallowed.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
AUH031	Contact with acid liberates toxic gas.

Precautionary statement(s) Prevention

P271 P280	Use only outdoors or in a well-ventilated area. Wear protective gloves, protective clothing, eye protection and face protection.
P261	Avoid breathing dust/fumes.
P264	Wash all exposed external body areas thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.

Precautionary statement(s) Response

P308+P313	IF exposed or concerned: Get medical advice/ attention.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider if you feel unwell.
P302+P352	IF ON SKIN: Wash with plenty of water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P330	Rinse mouth.
P332+P313	If skin irritation occurs: Get medical advice/attention.

Precautionary statement(s) Storage

P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

Precautionary statement(s) Disposal

Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

CAS No	%[weight]	Name
7757-83-7	>=95	Sodium Sulphite
Not Available		hydrolyses to
7446-09-5		sulfur dioxide

Legend: 1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L;

* EU IOELVs available

Mixtures

See section above for composition of Substances

SECTION 4 First aid measures

Chemwatch: 21891 Issue Date: 23/12/2022 Page 3 of 10 Print Date: 24/01/2024 Version No: 8.1

SODIUM SULPHITE

Eye Contact	If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin or hair contact occurs: Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor. Inhalation of vapours or aerosols (mists, fumes) may cause lung oedema. Corrosive substances may cause lung damage (e.g. lung oedema, fluid in the lungs). As this reaction may be delayed up to 24 hours after exposure, affected individuals need complete rest (preferably in semi-recumbent posture) and must be kept under medical observation even if no symptoms are (yet) manifested. Before any such manifestation, the administration of a spray containing a dexamethasone derivative or beclomethasone derivative may be considered. This must definitely be left to a doctor or person authorised by him/her. (ICSC13719)
Ingestion	 If SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY. For advice, contact a Poisons Information Centre or a doctor. Urgent hospital treatment is likely to be needed. In the mean time, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicated by the patient's condition. If the services of a medical officer or medical doctor are readily available, the patient should be placed in his/her care and a copy of the SDS should be provided. Further action will be the responsibility of the medical specialist. If medical attention is not available on the worksite or surroundings send the patient to a hospital together with a copy of the SDS. Where medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed otherwise: INDUCE vomiting with fingers down the back of the throat, ONLY IF CONSCIOUS. Lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. NOTE: Wear a protective glove when inducing vomiting by mechanical means.

Indication of any immediate medical attention and special treatment needed

As in all cases of suspected poisoning, follow the ABCDEs of emergency medicine (airway, breathing, circulation, disability, exposure), then the ABCDEs of toxicology (antidotes, basics, change absorption, change distribution, change elimination).

For poisons (where specific treatment regime is absent):

BASIC TREATMENT

Festablish a patent airway with suction where necessary.

- Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- Administer oxygen by non-rebreather mask at 10 to 15 L/min.
- Monitor and treat, where necessary, for pulmonary oedema.
- Monitor and treat, where necessary, for shock.
- Anticipate seizures
- DO NOT use emetics. Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.

ADVANCED TREATMENT

- F Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- ▶ Positive-pressure ventilation using a bag-valve mask might be of use.
- ▶ Monitor and treat, where necessary, for arrhythmias.
- Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema.
- Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- ► Treat seizures with diazepam.
- ▶ Proparacaine hydrochloride should be used to assist eye irrigation.

BRONSTEIN, A.C. and CURRANCE, P.L

EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

Treat symptomatically.

Depending on the degree of exposure, periodic medical examination is indicated. The symptoms of lung oedema often do not manifest until a few hours have passed and they are aggravated by physical effort. Rest and medical observation is therefore essential. Immediate administration of an appropriate spray, by a doctor or a person authorised by him/her should be considered.

(ICSC24419/24421

SECTION 5 Firefighting measures

Extinguishing media

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

Fire Incompatibility

None known.

Chemwatch: 21891 Version No: 8.1

Page 4 of 10

SODIUM SULPHITE

Issue Date: 23/12/2022 Print Date: 24/01/2024

Advice for firefighters

Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire. Prevent, by any means available, spillage from entering drains or water courses. Use fire fighting procedures suitable for surrounding area. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. Equipment should be thoroughly decontaminated after use.
Fire/Explosion Hazard	 Non combustible. Not considered a significant fire risk, however containers may burn. Decomposition may produce toxic fumes of: sulfur oxides (SOx) metal oxides May emit poisonous fumes.
HAZCHEM	Not Applicable

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Methods and material for cont	annion and clouming up
Minor Spills	 Remove all ignition sources. Clean up all spills immediately. Avoid contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Use dry clean up procedures and avoid generating dust. Place in a suitable, labelled container for waste disposal.
Major Spills	Moderate hazard. CAUTION: Advise personnel in area. Alert Emergency Services and tell them location and nature of hazard. Control personal contact by wearing protective clothing. Prevent, by any means available, spillage from entering drains or water courses. Recover product wherever possible. IF DRY: Use dry clean up procedures and avoid generating dust. Collect residues and place in sealed plastic bags or other containers for disposal.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Drocautione	for	cafo	handling	

Precautions for safe nandling	
Safe handling	 Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. DO NOT enter confined spaces until atmosphere has been checked. DO NOT allow material to contact humans, exposed food or food utensils. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke.
Other information	Consider storage under inert gas. Store in original containers. Keep containers securely sealed. Store in a cool, dry area protected from environmental extremes. Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this SDS. For major quantities: Consider storage in bunded areas - ensure storage areas are isolated from sources of community water (including stormwater, ground water, lakes and streams). Ensure that accidental discharge to air or water is the subject of a contingency disaster management plan; this may require consultation with local authorities.

Conditions for safe storage, including any incompatibilities

generate gaseous sulfur dioxide in contact with oxidising and nonoxidising acids

Chemwatch: 21891 Version No: 8.1

Page 5 of 10

Issue Date: 23/12/2022 Print Date: 24/01/2024

SODIUM SULPHITE

Sulfur dioxide:

- reacts with water or steam forming sulfurous acid; reaction may be violent
- reacts with acrolein, alcohols, aluminium powder, alkali metals, amines, bromine, pentafluoride, caustics, caesium, acetylene carbide, chlorates, chlorine trifluoride, chromium powder, copper or its alloy powders, diethylzinc, fluorine, lead dioxide, lithium acetylene carbide, metal powders, monolithium acetylide-ammonia, nitryl chloride, potassium acetylene carbide, potassium acetylide, potassium chlorate, rubidium carbide, silver azide, sodium, sodium acetylide, stannous oxide; reaction may be violent
- decomposes above 60 deg. C releasing oxides of sulfur
- Incompatible with alkalis, alkylene oxides, ammonia, aliphatic amines, alkanolamines, amides, organic anhydrides, caesium monoxide, epichlorohydrin, ferrous oxide, halogens, interhalogens, isocyanates, lithium nitrate, manganese, metal acetylides, metal oxides, perbromyl fluoride, red phosphorus, potassium azide, rubidium acetylide, sodium hydride, sulfuric acid
- attacks some plastics, coatings and rubber
- ▶ attacks metals, especially chemically active metals, in the presence of moisture.
- Contact with acids produces toxic fumes
- Metals and their oxides or salts may react violently with chlorine trifluoride and bromine trifluoride.
- These trifluorides are hypergolic oxidisers. They ignite on contact (without external source of heat or ignition) with recognised fuels contact with these materials, following an ambient or slightly elevated temperature, is often violent and may produce ignition.
- The state of subdivision may affect the results.
- Inorganic reducing agents react with oxidizing agents to generate heat and products that may be flammable, combustible, or otherwise reactive. Their reactions with oxidizing agents may be violent.
- Incidents involving interaction of active oxidants and reducing agents, either by design or accident, are usually very energetic and examples of so-called redox reactions.
- Segregate from alcohol, water.
- NOTE: May develop pressure in containers; open carefully. Vent periodically.

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	sulfur dioxide	Sulphur dioxide	2 ppm / 5.2 mg/m3	13 mg/m3 / 5 ppm	Not Available	Not Available

Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
Sodium Sulphite	11 mg/m3	120 mg/m3	710 mg/m3
sulfur dioxide	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
Sodium Sulphite	Not Available	Not Available
sulfur dioxide	100 ppm	Not Available

Occupational Exposure Banding

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
Sodium Sulphite	E	≤ 0.01 mg/m³
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.	

Exposure controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:

Appropriate engineering controls

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.

Employers may need to use multiple types of controls to prevent employee overexposure.

Local exhaust ventilation usually required

Individual protection measures, such as personal protective equipment











protective equipment

Eye and face protection

- ▶ "Safety glasses with side shields
- Chemical goggles

Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]"

Skin protection

See Hand protection below

SODIUM SULPHITE

Issue Date: 23/12/2022 Print Date: 24/01/2024

Hands/feet protection	The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended. Suitability and durability of glove type is dependent on usage. Experience indicates that the following polymers are suitable as glove materials for protection against undissolved, dry solids, where abrasive particles are not present. • polychloroprene. • nitrile rubber. • butyl rubber. • butyl rubber. • butyl rubber. • fluorocaoutchouc. • polyvinyl chloride. Gloves should be examined for wear and/ or degradation constantly.
Body protection	See Other protection below
Other protection	 Overalls. P.V.C apron. Barrier cream. Skin cleansing cream. Eye wash unit.

Respiratory protection

Type E-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	E P1 Air-line*	-	E PAPR-P1
up to 50 x ES	Air-line**	E P2	E PAPR-P2
up to 100 x ES	-	E P3	-
		Air-line*	-
100+ x ES	-	Air-line**	E PAPR-P3

* - Negative pressure demand ** - Continuous flow

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- · Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.
- · The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).
- · Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.
- · Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.
- · Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU)
- · Use approved positive flow mask if significant quantities of dust becomes airborne.
- · Try to avoid creating dust conditions.

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance Odourless, small white crystals or powder with saline sulfurous taste. Soluble in water and glycerol; almost insoluble in alcohol. A reducing agent. Exists in anhydrous form and as heptahydrate.			
Physical state	Divided Solid	Relative density (Water = 1)	2.63 (anhydrous)
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Applicable
pH (as supplied)	Not Applicable	Decomposition temperature (°C)	150
Melting point / freezing point (°C)	Decomposes.	Viscosity (cSt)	Not Applicable
Initial boiling point and boiling range (°C)	Decomposes.	Molecular weight (g/mol)	126.1 anhydrous
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Applicable	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Reacts	pH as a solution (1%)	9.6-9.8

SODIUM SULPHITE

Issue Date: 23/12/2022 Print Date: 24/01/2024

VOC g/L Vapour density (Air = 1) Not Applicable

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

or fumes, especially for prolonged periods, may produce respiratory discomfort and occasionally, distress.

SECTION 11 Toxicological information

Information	οn	toxico	Ionical	effects
IIIIOIIIIauoii	UII	LUXICU	iouicai	CHECLS

	Inhalation of dusts, generated by the material during the course of normal handling, may be damaging to the health of the individual.
Inhaled	Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur furth
	if excessive concentrations of particulate are inhaled.

and conditions such as emphysema or chronic bronchitis, may incur further disability If prior damage to the circulatory or nervous systems has occurred or if kidney damage has been sustained, proper screenings should be

The material is not thought to produce respiratory irritation (as classified by EC Directives using animal models). Nevertheless inhalation of dusts,

conducted on individuals who may be exposed to further risk if handling and use of the material result in excessive exposures. Sulfur dioxide is irritating. Short-term exposure causes constriction of the bronchi

The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.

Ingestion

Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.

Ingestion of sulfite salts may cause gastric irritation. Large doses may produce violent colic, diarrhoea, circulatory disturbance, depression of vital functions and, sometimes, death,

Skin Contact

Open cuts, abraded or irritated skin should not be exposed to this material

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

This material can cause inflammation of the skin on contact in some persons.

Eye

This material can cause eve irritation and damage in some persons.

Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may cause transient discomfort characterised by tearing or conjunctival redness (as with windburn). Slight abrasive damage may also result.

Chronic

Strong evidence exists that this substance may cause irreversible mutations (though not lethal) even following a single exposure. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. Sulfites and bisulfites can cause narrowing of the airways, stomach upset, flushing, low blood pressure, tingling sensation, itchy wheal, swelling and shock, and asthmatics are especially prone. They induce allergic-like reactions which can occur on first contact with the material. Long term exposure to high dust concentrations may cause changes in lung function i.e. pneumoconiosis, caused by particles less than 0.5 micron penetrating and remaining in the lung.

Chronic explosure to sulfur dioxide (SO2) particle complexes in polluted air can aggravate chronic disease, such as asthma, chronic pulmonary disease, and coronary artery disease. It is not clear what is the concentration level required to cause these effects.

Animal testing showed that simultaneous exposure to benz(a)pyrene and sulfur dioxide increases the rate of cancer development compared to exposure to only one of the above substances.

There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment

Sodium Sulphite

TOXICITY	IRRITATION
dermal (rat) LD50: >2000 mg/kg[1]	Not Available
Inhalation(Rat) LC50: >5.5 mg/l4h ^[2]	
Oral (Mouse) LD50; 820 mg/kg ^[2]	

sulfur dioxide

TOXICITY	IRRITATION
Inhalation(Rat) LC50: 1260 ppm4h ^[2]	Eye: adverse effect observed (irritating) ^[1]
	Skin: adverse effect observed (corrosive) ^[1]
	Skin: adverse effect observed (irritating) ^[1]

Legend:

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

SODIUM SULPHITE

The substance is classified by IARC as Group 3:

NOT classifiable as to its carcinogenicity to humans.

Evidence of carcinogenicity may be inadequate or limited in animal testing.

SULFUR DIOXIDE

DIOXIDE

respiratory disease - condition aggravated by smoking. The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

400-500 ppm - immediately dangerous to life. NOTE: Aggravates chronic pulmonary disease and increases the risk of acute and chronic

SODIUM SULPHITE & SULFUR

Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent

Page 8 of 10

SODIUM SULPHITE

Issue Date: **23/12/2022**Print Date: **24/01/2024**

asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production.

Acute Toxicity	✓	Carcinogenicity	×
Skin Irritation/Corrosion	✓	Reproductivity	×
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✓
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	✓	Aspiration Hazard	X

Leaend:

X − Data either not available or does not fill the criteria for classification
 ✓ − Data available to make classification

SECTION 12 Ecological information

Toxicity

	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	43.8mg/l	2
	EC50	48h	Crustacea	89mg/l	2
Sodium Sulphite	EC50	96h	Algae or other aquatic plants	48mg/l	2
	ErC50	72h	Algae or other aquatic plants	447.8mg/l	2
	NOEC(ECx)	504h	Crustacea	>10mg/l	2
	LC50	96h	Fish	147-215mg/l	2
	Endpoint	Test Duration (hr)	Species	Value	Source
sulfur dioxide	Not Available	Not Available	Not Available	Not Available	Not Available
Legend:	Ecotox databas		egistered Substances - Ecotoxicological Informa tic Hazard Assessment Data 6. NITE (Japan) - E		

For Sulfur Dioxide (SO2): Vapor Pressure: 3,000 mm Hg @ 20 C; Henry s Law Constant: 1.23 mol.L-1/atm-1 @ 25C.

Environmental Fate: Natural sources of sulfur dioxide include volcanoes and volcanic vents, decaying organic matter, solar action on seawater and oxidation of dimethyl sulfide emitted from the ocean. On a global scale, man-made emissions represent a significant contribution to the SO2 emitted to the atmosphere and these emissions are approximately equal to natural emissions.

Atmospheric Fate: Sulfur dioxide is typically present in a gaseous phase and, once released into the atmosphere, may be converted to other compounds, and/or removed from the atmosphere by various mechanisms. Processes such as oxidation, wet deposition, dry deposition, absorption by vegetation and by soil, dissolution into water and other processes contribute to the removal of SO2 from the atmosphere. In the atmosphere, sulfur dioxide can be transformed into sulfuric acid or sulfates, by a variety of processes, or oxidized to sulfur trioxide, (SO3), and sulfate. This substance reacts with free radicals to form ozone and alkene gasses. SO2 is expected to be oxidized by sunlight in the atmosphere.

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
sulfur dioxide	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
sulfur dioxide	LOW (LogKOW = -2.2002)

Mobility in soil

Ingredient	Mobility
sulfur dioxide	MEDIUM (KOC = 2.989)

SECTION 13 Disposal considerations

Waste treatment methods

- Containers may still present a chemical hazard/ danger when empty.
- Return to supplier for reuse/ recycling if possible.

Otherwise:

If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.

Product / Packaging disposal

Where possible retain label warnings and SDS and observe all notices pertaining to the product.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- ► Reduction
- ► Reuse

Page 9 of 10

SODIUM SULPHITE

Issue Date: 23/12/2022 Print Date: 24/01/2024

- Recycling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate. In most instances the supplier of the material should be consulted.

- DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- ▶ Where in doubt contact the responsible authority.
- ▶ Recycle wherever possible or consult manufacturer for recycling options.
- ► Consult State Land Waste Management Authority for disposal.
- ▶ Bury residue in an authorised landfill.
- ► Recycle containers if possible, or dispose of in an authorised landfill.

SECTION 14 Transport information

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
Sodium Sulphite	Not Available
sulfur dioxide	Not Available

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
Sodium Sulphite	Not Available
sulfur dioxide	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

Sodium Sulphite is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australian Inventory of Industrial Chemicals (AIIC)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

sulfur dioxide is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australian Inventory of Industrial Chemicals (AIIC)

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

Additional Regulatory Information

Not Applicable

National Inventory Status

National Inventory Status		
National Inventory	Status	
Australia - AIIC / Australia Non-Industrial Use	Yes	
Canada - DSL	Yes	
Canada - NDSL	No (Sodium Sulphite; sulfur dioxide)	
China - IECSC	Yes	
Europe - EINEC / ELINCS / NLP	Yes	
Japan - ENCS	Yes	
Korea - KECI	Yes	
New Zealand - NZIoC	Yes	
Philippines - PICCS	Yes	
USA - TSCA	Yes	

Chemwatch: 21891
Version No: 8.1

Page 10 of 10 SODIUM SULPHITE

Issue Date: 23/12/2022 Print Date: 24/01/2024

National Inventory	Status		
Taiwan - TCSI	Yes		
Mexico - INSQ	Yes		
Vietnam - NCI	Yes		
Russia - FBEPH	Yes		
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.		

SECTION 16 Other information

Revision Date	23/12/2022
Initial Date	24/10/2005

SDS Version Summary

Version	Date of Update	Sections Updated
8.1	23/12/2022	Classification review due to GHS Revision change.

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

- ▶ PC TWA: Permissible Concentration-Time Weighted Average
- ▶ PC STEL: Permissible Concentration-Short Term Exposure Limit
- ► IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists
- ▶ STEL: Short Term Exposure Limit
- ► TEEL: Temporary Emergency Exposure Limit。
- ▶ IDLH: Immediately Dangerous to Life or Health Concentrations
- ► ES: Exposure Standard
- ► OSF: Odour Safety Factor
- ▶ NOAEL: No Observed Adverse Effect Level
- ▶ LOAEL: Lowest Observed Adverse Effect Level
- ► TLV: Threshold Limit Value
- ► LOD: Limit Of Detection
- ► OTV: Odour Threshold Value
- ► BCF: BioConcentration Factors
- BEI: Biological Exposure IndexDNEL: Derived No-Effect Level
- ► PNEC: Predicted no-effect concentration
- ▶ AIIC: Australian Inventory of Industrial Chemicals
- ▶ DSL: Domestic Substances List
- NDSL: Non-Domestic Substances List
- ▶ IECSC: Inventory of Existing Chemical Substance in China
- ► EINECS: European INventory of Existing Commercial chemical Substances
- ► ELINCS: European List of Notified Chemical Substances
- NLP: No-Longer Polymers
- ► ENCS: Existing and New Chemical Substances Inventory
- KECI: Korea Existing Chemicals Inventory
- ► NZIoC: New Zealand Inventory of Chemicals
- PICCS: Philippine Inventory of Chemicals and Chemical Substances
- ► TSCA: Toxic Substances Control Act
- TCSI: Taiwan Chemical Substance Inventory
- INSQ: Inventario Nacional de Sustancias Químicas
- ► NCI: National Chemical Inventory
- FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.