

# Arcotest Test Pen PINK 38 mN/m

# **ALPHA CHEMICALS PTY LTD**

Chemwatch: **5396-12** Version No: **2.1.1.1** 

Safety Data Sheet according to WHS and ADG requirements

# Chemwatch Hazard Alert Code: 2

Issue Date: **22/04/2020**Print Date: **22/04/2020**S.GHS.AUS.EN

## SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

#### **Product Identifier**

Product name	Arcotest Test Pen PINK 38 mN/m
Synonyms	Not Available
Other means of identification	Not Available

## Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Determination of the surface tension and surface cleanliness of solids (films / moulded parts) made of plastic, metal, glass etc.

# Details of the supplier of the safety data sheet

Registered company name	ALPHA CHEMICALS PTY LTD
Address	4 ALLEN PLACE WETHERILL PARK NSW 2099 Australia
Telephone	61 (0)2 9982 4622
Fax	Not Available
Website	~
Email	shane@alphachem.com.au

# Emergency telephone number

Association / Organisation	ALPHA CHEMICALS PTY LTD
Emergency telephone numbers	61 (0)418 237 771
Other emergency telephone numbers	Not Available

# **SECTION 2 HAZARDS IDENTIFICATION**

# Classification of the substance or mixture

# HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

## CHEMWATCH HAZARD RATINGS

	Min	Max	
Flammability	1		
Toxicity	2		0 = Minimum
Body Contact	2		1 = Low 2 = Moderate
Reactivity	1		3 = High
Chronic	2		4 = Extreme

Poisons Schedule	Not Applicable
Classification <sup>[1]</sup>	Acute Toxicity (Oral) Category 4, Skin Corrosion/Irritation Category 2, Eye Irritation Category 2A, Specific target organ toxicity - repeated exposure Category 2
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

## Label elements

Hazard pictogram(s)





SIGNAL WORD WARNING

Hazard statement(s)

H302 Harmful if swallowed.

Chemwatch: 5396-12 Page 2 of 9

Version No: 2.1.1.1

## Arcotest Test Pen PINK 38 mN/m

Issue Date: 22/04/2020 Print Date: 22/04/2020

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H373	May cause damage to organs through prolonged or repeated exposure.

## Precautionary statement(s) Prevention

P260	Do not breathe mist/vapours/spray.
P270	Do not eat, drink or smoke when using this product.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

# Precautionary statement(s) Response

P321	Specific treatment (see advice on this label).
P362	Take off contaminated clothing and wash before reuse.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314	Get medical advice/attention if you feel unwell.
P337+P313	If eye irritation persists: Get medical advice/attention.
P301+P312	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
P302+P352	IF ON SKIN: Wash with plenty of water.
P330	Rinse mouth.

# Precautionary statement(s) Storage

Not Applicable

## Precautionary statement(s) Disposal

P501

Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

# **SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS**

#### Substances

See section below for composition of Mixtures

# Mixtures

CAS No	%[weight]	Name
111-46-6	10-97	diethylene glycol
107-41-5	3-90	hexylene glycol

## **SECTION 4 FIRST AID MEASURES**

# D

Description of first aid measures		
Eye Contact	If this product comes in contact with the eyes:  • Wash out immediately with fresh running water.  • Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.  • Seek medical attention without delay; if pain persists or recurs seek medical attention.  • Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.	
Skin Contact	If skin contact occurs:  Immediately remove all contaminated clothing, including footwear.  Flush skin and hair with running water (and soap if available).  Seek medical attention in event of irritation.	
Inhalation	<ul> <li>If fumes or combustion products are inhaled remove from contaminated area.</li> <li>Lay patient down. Keep warm and rested.</li> <li>Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>Transport to hospital, or doctor.</li> </ul>	
	IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY.      For advice, contact a Poisons Information Centre or a doctor.      Urgent hospital treatment is likely to be needed.      In the mean time, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicated by the patient's condition.      If the services of a medical officer or medical doctor are readily available, the patient should be placed in his/her care and a copy of the SDS should be provided. Further action will be the responsibility of the medical specialist.	

- should be provided. Further action will be the responsibility of the medical specialist.
- If medical attention is not available on the worksite or surroundings send the patient to a hospital together with a copy of the SDS.

#### Where medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed otherwise:

► INDUCE vomiting with fingers down the back of the throat, ONLY IF CONSCIOUS. Lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.

NOTE: Wear a protective glove when inducing vomiting by mechanical means.

Ingestion

Chemwatch: 5396-12 Page 3 of 9

#### Arcotest Test Pen PINK 38 mN/m

Issue Date: **22/04/2020**Print Date: **22/04/2020** 

Treat symptomatically.

Version No: 2.1.1.1

- ▶ Polyethylene glycols are generally poorly absorbed orally and are mostly unchanged by the kidney.
- ▶ Dermal absorption can occur across damaged skin (e.g. through burns) leading to increased osmolality, anion gap metabolic acidosis, elevated calcium, low ionised calcium, CNS depression and renal failure.
- ► Treatment consists of supportive care.

[Ellenhorn and Barceloux: Medical Toxicology]

# **SECTION 5 FIREFIGHTING MEASURES**

## **Extinguishing media**

- ▶ Alcohol stable foam.
- ► Dry chemical powder.
- ▶ BCF (where regulations permit).
- Carbon dioxide.
- ▶ Water spray or fog Large fires only.

#### Special hazards arising from the substrate or mixture

Special nazards arising from the substrate or mixture		
Fire Incompatibility	▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result	
Advice for firefighters		
Fire Fighting	<ul> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear full body protective clothing with breathing apparatus.</li> <li>Prevent, by any means available, spillage from entering drains or water course.</li> <li>Use water delivered as a fine spray to control fire and cool adjacent area.</li> <li>Avoid spraying water onto liquid pools.</li> <li>DO NOT approach containers suspected to be hot.</li> <li>Cool fire exposed containers with water spray from a protected location.</li> <li>If safe to do so, remove containers from path of fire.</li> </ul>	
Fire/Explosion Hazard	<ul> <li>Combustible.</li> <li>Slight fire hazard when exposed to heat or flame.</li> <li>Heating may cause expansion or decomposition leading to violent rupture of containers.</li> <li>On combustion, may emit toxic fumes of carbon monoxide (CO).</li> <li>May emit acrid smoke.</li> <li>Mists containing combustible materials may be explosive.</li> <li>Combustion products include:</li> <li>carbon dioxide (CO2)</li> <li>other pyrolysis products typical of burning organic material.</li> <li>May emit poisonous fumes.</li> <li>May emit corrosive fumes.</li> </ul>	
HAZCHEM	Not Applicable	

# **SECTION 6 ACCIDENTAL RELEASE MEASURES**

## Personal precautions, protective equipment and emergency procedures

See section 8

# **Environmental precautions**

See section 12

# Methods and material for containment and cleaning up

Minor Spills	Slippery when spilt.  Remove all ignition sources.  Clean up all spills immediately.  Avoid breathing vapours and contact with skin and eyes.  Control personal contact with the substance, by using protective equipment.  Contain and absorb spill with sand, earth, inert material or vermiculite.  Wipe up.  Place in a suitable, labelled container for waste disposal.
Major Spills	Slippery when spilt.  Moderate hazard.  Clear area of personnel and move upwind.  Alert Fire Brigade and tell them location and nature of hazard.  Wear breathing apparatus plus protective gloves.  Prevent, by any means available, spillage from entering drains or water course.  No smoking, naked lights or ignition sources.  Increase ventilation.  Stop leak if safe to do so.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

# **SECTION 7 HANDLING AND STORAGE**

# Precautions for safe handling

DO NOT allow clothing wet with material to stay in contact with skin
 Avoid all personal contact, including inhalation

- Safe handling

  Avoid all personal contact, including inhalation.

  Week protective elething when risk of exposure
  - ► Wear protective clothing when risk of exposure occurs.
  - ► Use in a well-ventilated area.

Chemwatch: 5396-12 Page 4 of 9

Arcotest Test Pen PINK 38 mN/m

Issue Date: 22/04/2020 Print Date: 22/04/2020

Prevent concentration in hollows and sumps.

- DO NOT enter confined spaces until atmosphere has been checked.
- Avoid smoking, naked lights or ignition sources.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke

#### Consider storage under inert gas

- ▶ Material is hygroscopic, i.e. absorbs moisture from the air. Keep containers well sealed in storage.
- ▶ Store in original containers.
- ► Keep containers securely sealed.
- No smoking, naked lights or ignition sources.
- ▶ Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers
- ▶ Protect containers against physical damage and check regularly for leaks.
- ▶ Observe manufacturer's storage and handling recommendations contained within this SDS.

#### Conditions for safe storage, including any incompatibilities

#### Suitable container

Storage incompatibility

Other information

- Metal can or drum
- Packaging as recommended by manufacturer.
- ▶ Check all containers are clearly labelled and free from leaks.

## ▶ Glycols and their ethers undergo violent decomposition in contact with 70% perchloric acid. This seems likely to involve formation of the glycol perchlorate esters (after scission of ethers) which are explosive, those of ethylene glycol and 3-chloro-1,2-propanediol being more powerful than glyceryl nitrate, and the former so sensitive that it explodes on addition of water.

#### Hexylene glycol:

• is incompatible with strong oxidisers, sulfuric acid, nitric acid, caustics, aliphatic amines, isocyanates

#### Alcohols

• are incompatible with strong acids, acid chlorides, acid anhydrides, oxidising and reducing agents.

- reacts, possibly violently, with alkaline metals and alkaline earth metals to produce hydroger
- react with strong acids, strong caustics, aliphatic amines, isocyanates, acetaldehyde, benzoyl peroxide, chromic acid, chromium oxide, dialkylzincs, dichlorine oxide, ethylene oxide, hypochlorous acid, isopropyl chlorocarbonate, lithium tetrahydroaluminate, nitrogen dioxide, pentafluoroguanidine, phosphorus halides, phosphorus pentasulfide, tangerine oil, triethylaluminium, triisobutylaluminium
- should not be heated above 49 deg. C. when in contact with aluminium equipment
- Avoid strong acids, bases.

## **SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION**

## **Control parameters**

Version No: 2.1.1.1

#### OCCUPATIONAL EXPOSURE LIMITS (OEL)

## INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	diethylene glycol	2,2'-Oxybis[ethanol]	23 ppm / 100 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	hexylene glycol	Hexylene glycol	Not Available	Not Available	25 ppm / 121 mg/m3	Not Available

## **EMERGENCY LIMITS**

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
diethylene glycol	Diethylene glycol	6.9 ppm	140 ppm	860 ppm
hexylene glycol	Hexylene glycol	2.3 ppm	25 ppm	150 ppm

Ingredient	Original IDLH	Revised IDLH
diethylene glycol	Not Available	Not Available
hexylene glycol	Not Available	Not Available

# **Exposure controls**

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk. Appropriate engineering

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure

Local exhaust ventilation usually required

# Personal protection

controls







a clean environment only after workers have washed hands thoroughly.



- Safety glasses with side shields
- Chemical goggles

#### Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in

# Skin protection

Eye and face protection

See Hand protection below

# Chemwatch: **5396-12** Version No: **2.1.1.1**

#### Arcotest Test Pen PINK 38 mN/m

Issue Date: **22/04/2020**Print Date: **22/04/2020** 

#### ▶ Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application Hands/feet protection The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended. Suitability and durability of glove type is dependent on usage. **Body protection** See Other protection below Overalls. P.V.C. apron. Other protection Barrier cream. Skin cleansing cream. ▶ Eye wash unit.

## Recommended material(s)

## GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

#### "Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the *computer-generated* selection:

Arcotest Test Pen PINK 38 mN/m

Material	CPI
BUTYL	Α
NITRILE	A

- \* CPI Chemwatch Performance Index
- A: Best Selection
- B: Satisfactory; may degrade after 4 hours continuous immersion
- C: Poor to Dangerous Choice for other than short term immersion

**NOTE**: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

# Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 5 x ES	A-AUS / Class 1 P2	-	A-PAPR-AUS / Class 1 P2
up to 25 x ES	Air-line*	A-2 P2	A-PAPR-2 P2
up to 50 x ES	-	A-3 P2	-
50+ x ES	-	Air-line**	-

#### ^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

# **SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES**

## Information on basic physical and chemical properties

Appearance	Pink liquid with no odour; mixes with water.		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	-1.98 - 0.58
Odour threshold	Not Available	Auto-ignition temperature (°C)	355-425
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	-406	Viscosity (cSt)	36-45 @20C
Initial boiling point and boiling range (°C)	196-252	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	93-138	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	9.9-12.2	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	1-1.8	Volatile Component (%vol)	100 (VOC)
Vapour pressure (kPa)	0.008-0.07 @20C	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	6-8 @20C (20%)
Vapour density (Air = 1)	>1	VOC g/L	Not Available

Page 6 of 9

Arcotest Test Pen PINK 38 mN/m

Issue Date: **22/04/2020**Print Date: **22/04/2020** 

# **SECTION 10 STABILITY AND REACTIVITY**

Reactivity	See section 7
Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

# **SECTION 11 TOXICOLOGICAL INFORMATION**

## Information on toxicological effects

Inhaled	Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.  Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.  Aliphatic alcohols with more than 3-carbons cause headache, dizziness, drowsiness, muscle weakness and delirium, central depression, coma, seizures and behavioural changes. Secondary respiratory depression and failure, as well as low blood pressure and irregular heart rhythms, may follow.		
Ingestion	Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.  If swallowed, the toxic effects of glycols (dihydric alcohols) are similar to those of alcohol, with depression of the central nervous system, nausea, vomiting, and degenerative changes in the liver and kidney.  Overexposure to non-ring alcohols causes nervous system symptoms. These include headache, muscle weakness and inco-ordination, giddiness, confusion, delirium and coma.  Symptoms of over-exposure to hexylene glycol include stimulation of the central nervous system followed by depression, drowsiness, vomiting, coma, failure of breathing, convulsions, kidney damage and death. It is eliminated in the urine.		
Skin Contact	When hexylene glycol was applied as a dressing to paedia almost half of the comatose group eventually dying as a re Most liquid alcohols appear to act as primary skin irritants man.  Open cuts, abraded or irritated skin should not be exposed Entry into the blood-stream, through, for example, cuts, ab prior to the use of the material and ensure that any external	ne individual; systemic effects may result following absorption.  atric burn patients, approximately 8% exhibited highly variable periods of coma with  ssult of kidney failure.  in humans. Significant percutaneous absorption occurs in rabbits but not apparently in  d to this material  brasions or lesions, may produce systemic injury with harmful effects. Examine the skir  al damage is suitably protected.  n either following direct contact or after a delay of some time. Repeated exposure can	
Eye	There is evidence that material may produce eye irritation inflammation may be expected with pain.	in some persons and produce eye damage 24 hours or more after instillation. Severe	
Chronic	Harmful: danger of serious damage to health by prolonged This material can cause serious damage if one is exposed produce severe defects.	d exposure through inhalation, in contact with skin and if swallowed. It to it for long periods. It can be assumed that it contains a substance which can to this material may result in toxic effects to the unborn baby.	
Assert and Total Day DINII 00	TOXICITY	IRRITATION	
Arcotest Test Pen PINK 38 mN/m	Not Available	Not Available	
	TOXICITY	IRRITATION	
	Dermal (rabbit) LD50: 11890 mg/kg <sup>[2]</sup>	Eye (rabbit) 50 mg mild	
	Oral (rat) LD50: 12000 mg/kg <sup>[2]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>	
diethylene glycol		Skin (human): 112 mg/3d-l mild	
		Skin (rabbit): 500 mg mild	
	4 =		
		Skin: no adverse effect observed (not irritating) <sup>[1]</sup>	
	TOXICITY	Skin: no adverse effect observed (not irritating) <sup>[1]</sup> IRRITATION	
	TOXICITY  Dermal (rabbit) LD50: >5000 mg/kg <sup>[2]</sup>	'	
		IRRITATION	
hexylene glycol	Dermal (rabbit) LD50: >5000 mg/kg <sup>[2]</sup>	IRRITATION Eye (rabbit): 93mg - SEVERE	
hexylene glycol	Dermal (rabbit) LD50: >5000 mg/kg <sup>[2]</sup>	IRRITATION  Eye (rabbit): 93mg - SEVERE  Eye: no adverse effect observed (not irritating) <sup>[1]</sup>	
hexylene glycol	Dermal (rabbit) LD50: >5000 mg/kg <sup>[2]</sup>	IRRITATION  Eye (rabbit): 93mg - SEVERE  Eye: no adverse effect observed (not irritating) <sup>[1]</sup> Skin (rabbit):465 mg open-mild	

Chemwatch: 5396-12 Page 7 of 9

Version No: 2.1.1.1

## Arcotest Test Pen PINK 38 mN/m

Issue Date: **22/04/2020**Print Date: **22/04/2020** 

DIETHYLENE GLYCOL	The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.  Diglycolic acid is formed following the oxidation of accidentally ingested diethylene glycol in the body and can lead to severe complications with fatal outcome.		
HEXYLENE GLYCOL	Hexylene glycol is of low acute toxicity but may be acutely lethal at very high doses. It may cause reversible irritation of the skin and eye. Repeated exposure may cause irreversible damage to the liver and stomach and partly reversible kidney damage. It is likely not to cause mutations or affect reproduction or development of the unborn.		
Acute Toxicity	✓	Carcinogenicity	×
Skin Irritation/Corrosion	✓	Reproductivity	×
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	<b>✓</b>
Mutagenicity	x	Aspiration Hazard	×

Legend:

★ - Data either not available or does not fill the criteria for classification

– Data available to make classification

# **SECTION 12 ECOLOGICAL INFORMATION**

## Toxicity

Arcotest Test Pen PINK 38 mN/m	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	66-mg/L	2
diethylene glycol	EC50	48	Crustacea	=84000mg/L	1
	EC50	96	Algae or other aquatic plants	9-362mg/L	2
	NOEC	552	Crustacea	>=1-mg/L	2
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURC
	LC50	96	Fish	8-mg/L	2
hexylene glycol	EC50	48	Crustacea	2-800mg/L	2
	EC50	72	Algae or other aquatic plants	>429mg/L	2
	NOEC	72	Algae or other aquatic plants	429mg/L	2

Legend:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

# DO NOT discharge into sewer or waterways.

# Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
diethylene glycol	LOW	LOW
hexylene glycol	LOW	LOW

# **Bioaccumulative potential**

Ingredient	Bioaccumulation
diethylene glycol	LOW (BCF = 180)
hexylene glycol	LOW (LogKOW = 0.5802)

# Mobility in soil

Ingredient	Mobility
diethylene glycol	HIGH (KOC = 1)
hexylene glycol	HIGH (KOC = 1)

## **SECTION 13 DISPOSAL CONSIDERATIONS**

## Waste treatment methods

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.

## Product / Packaging disposal

- Where in doubt contact the responsible authority.
   Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Authority for disposal.
- ▶ Bury or incinerate residue at an approved site.

Page 8 of 9

Arcotest Test Pen PINK 38 mN/m

Issue Date: 22/04/2020 Print Date: 22/04/2020

▶ Recycle containers if possible, or dispose of in an authorised landfill.

## **SECTION 14 TRANSPORT INFORMATION**

## **Labels Required**

**Marine Pollutant** NO

**HAZCHEM** Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

## **SECTION 15 REGULATORY INFORMATION**

Safety, health and environmental regulations / legislation specific for the substance or mixture

#### DIETHYLENE GLYCOL IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals Australia Inventory of Chemical Substances (AICS)

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -Schedule 5

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -Schedule 6

#### HEXYLENE GLYCOL IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australia Inventory of Chemical Substances (AICS)

#### **National Inventory Status**

National Inventory	Status
Australia - AICS	Yes
Canada - DSL	Yes
Canada - NDSL	No (diethylene glycol; hexylene glycol)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - ARIPS	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

# **SECTION 16 OTHER INFORMATION**

Revision Date	22/04/2020
Initial Date	22/04/2020

## Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

## **Definitions and abbreviations**

PC-TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancel

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level Chemwatch: 5396-12 Page 9 of 9 Issue Date: 22/04/2020 Version No: 2.1.1.1 Print Date: 22/04/2020

Arcotest Test Pen PINK 38 mN/m

TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.
TEL (+61 3) 9572 4700.