

# Manganese Nitrate 50% solution **ALPHA CHEMICALS PTY LTD**

Chemwatch Hazard Alert Code: 2

Ch	em	vatch	5500	-25

Version No: 5.1 Safety Data Sheet according to WHS Regulations (Hazardous Chemicals) Amendment 2020 and ADG requirements Issue Date: 23/12/2022 Print Date: 21/01/2024 S.GHS.AUS.EN

### SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier	
Product name	Manganese Nitrate 50% solution
Chemical Name	Not Applicable
Synonyms	Mn(NO3)2 solution; manganous nitrate solution
Proper shipping name	MANGANESE NITRATE
Chemical formula	Not Applicable
Other means of identification	Not Available

#### Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Intermediate in manufacture of reagent grade manganese dioxide and in the preparation of porcelain colourants.

### Details of the manufacturer or supplier of the safety data sheet

Registered company name	ALPHA CHEMICALS PTY LTD
Address	4 ALLEN PLACE WETHERILL PARK NSW 2164 Australia
Telephone	61 (0)2 9982 4622
Fax	Not Available
Website	~
Email	shane@alphachem.com.au

#### Emergency telephone number

Association / Organisation	ALPHA CHEMICALS PTY LTD	CHEMWATCH EMERGENCY RESPONSE (24/7)
Emergency telephone numbers	61 (0)418 237 771	+61 1800 951 288
Other emergency telephone numbers	Not Available	+61 3 9573 3188

#### Once connected and if the message is not in your preferred language then please dial 01

#### **SECTION 2 Hazards identification**

#### Classification of the substance or mixture

### HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

### Chemwatch Hazard Ratings

	Min	Max	
Flammability	1		
Toxicity	2		0 = Minimum
Body Contact	2	1	1 = Low
Reactivity	2		2 = Moderate
Chronic	0	1	3 = High 4 = Extreme

Poisons Schedule	Not Applicable
Classification <sup>[1]</sup>	Acute Toxicity (Oral) Category 4, Skin Corrosion/Irritation Category 1A, Serious Eye Damage/Eye Irritation Category 1, Acute Toxicity (Inhalation) Category 4, Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, Carcinogenicity Category 2, Hazardous to the Aquatic Environment Acute Hazard Category 3
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI



Signal word Danger

#### Hazard statement(s)

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H402	Harmful to aquatic life.

#### Precautionary statement(s) Prevention

P201	Obtain special instructions before use.
P260	Do not breathe mist/vapours/spray.
P264	Wash all exposed external body areas thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves, protective clothing, eye protection and face protection.
P270	Do not eat, drink or smoke when using this product.
P273	Avoid release to the environment.

### Precautionary statement(s) Response

P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If more than 15 mins from Doctor, INDUCE VOMITING (if conscious).		
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].		
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.		
P308+P313	IF exposed or concerned: Get medical advice/ attention.		
P310	Immediately call a POISON CENTER/doctor/physician/first aider.		
P363	Wash contaminated clothing before reuse.		
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider if you feel unwell.		
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.		

### Precautionary statement(s) Storage

P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

### Precautionary statement(s) Disposal

P501

Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

### **SECTION 3 Composition / information on ingredients**

#### Substances

See section below for composition of Mixtures

### Mixtures

CAS No	%[weight]	Name
10377-66-9	30-60	manganese nitrate
7732-18-5	>60	Distilled Water
Legend:	1. Classified by Chernwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available	

### **SECTION 4 First aid measures**

Description of first aid measures			
Eye Contact	<ul> <li>If this product comes in contact with the eyes:</li> <li>Wash out immediately with fresh running water.</li> <li>Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>Seek medical attention without delay; if pain persists or recurs seek medical attention.</li> <li>Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>		

Comments

B.NS.SQ

#### Manganese Nitrate 50% solution

Skin Contact	If skin contact occurs: <ul> <li>Immediately remove all contaminated clothing, including footwear.</li> <li>Flush skin and hair with running water (and soap if available).</li> <li>Seek medical attention in event of irritation.</li> </ul>
Inhalation	<ul> <li>If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>Other measures are usually unnecessary.</li> </ul>
Ingestion	If poisoning occurs, contact a doctor or Poisons Information Centre.  If SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY. For advice, contact a Poisons Information Centre or a doctor. Where Medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed otherwise: Induce vomiting with fingers down the back of the of the throat, ONLY IF CONSCIOUS. Lean patient forward or place on left side (head-down position if possible) to maintain open airway and prevent aspiration. NOTE: Wear a protective glove when inducing vomiting by mechanical means. In the mean time, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicated by the patient's condition. If the services of a medical officer or medical doctor are readily available, the patient should be placed in his/her care and a copy of the SDS should be provided. Further action will be the responsibility of the medical specialist. If medical attention is not available on the worksite or surroundings send the patient to a hospital together with a copy of the SDS.

#### Indication of any immediate medical attention and special treatment needed

The toxicity of nitrates and nitrites result from their vasodilating properties and their propensity to form methaemoglobin.

- Most produce a peak effect within 30 minutes.
- ٠ Clinical signs of cyanosis appear before other symptoms because of the dark pigmentation of methaemoglobin.
- Initial attention should be directed towards improving oxygen delivery, with assisted ventilation, if necessary. Hyperbaric oxygen has not demonstrated conclusive benefits.
- ۲ Institute cardiac monitoring, especially in patients with coronary artery or pulmonary disease.
- Hypotension should respond to Trendelenburg's position and intravenous fluids; otherwise dopamine may be needed.
- ۲ Naloxone, glucose and thiamine should be given if a multiple ingestion is suspected.
- Decontaminate using Ipecac Syrup for alert patients or lavage for obtunded patients who present within 2-4 hours of ingestion.
- Symptomatic patients with methaemoglobin levels over 30% should receive methylene blue. (Cyanosis alone, is not an indication for treatment). The usual dose is 1-2 mg/kg of a 1% solution (10 mg/ml) IV over 5 minutes; repeat, using the same dose if symptoms of hypoxia fail to subside within 1 hour.

#### [Ellenhorn and Barceloux: Medical Toxicology]

**BIOLOGICAL EXPOSURE INDEX - BEI** 

These represent the determinants observed in specimens collected from a healthy worker who has been exposed at the Exposure Standard (ES or TLV):

Determinant 1. Methaemoglobin in blood

٠

1.5% of haemoglobin

Sampling Time

During or end of shift

B: Background levels occur in specimens collected from subjects NOT exposed

NS: Non-specific determinant; also observed after exposure to other materials

SQ: Semi-quantitative determinant - Interpretation may be ambiguous; should be used as a screening test or confirmatory test.

Index

Both dermal and oral toxicity of manganese salts is low because of limited solubility of manganese. No known permanent pulmonary sequelae develop after acute manganese exposure. Treatment is supportive.

[Ellenhorn and Barceloux: Medical Toxicology]

In clinical trials with miners exposed to manganese-containing dusts, L-dopa relieved extrapyramidal symptoms of both hypo kinetic and dystonic patients. For short periods of time symptoms could also be controlled with scopolamine and amphetamine. BAL and calcium EDTA prove ineffective.

[Gosselin et al: Clinical Toxicology of Commercial Products.]

#### **SECTION 5 Firefighting measures**

#### Extinguishing media

- Jets of water
- Water spray or fog.
- Foam.
- Dry chemical powder. ٠
- BCF (where regulations permit).
- Carbon dioxide.

#### Special hazards arising from the substrate or mixture

Fire Incompatibility	Oxidising agents as a class are not necessarily combustible themselves, but can increase the risk and intensity of fire in many other substances.
Advice for firefighters	
	<ul> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>May be violently or explosively reactive.</li> </ul>
	<ul> <li>Wear breathing apparatus plus protective gloves.</li> </ul>
Fire Fighting	<ul> <li>Prevent, by any means available, spillage from entering drains or water course.</li> <li>Eicht für form a sofe dictage with adapted available available.</li> </ul>

- Fight fire from a safe distance, with adequate cover.
  - Extinguishers should be used only by trained personnel
  - · Use water delivered as a fine spray to control fire and cool adjacent area.
  - Avoid spraying water onto liquid pools.

Fire/Explosion Hazard	<ul> <li>Will not burn but increases intensity of fire.</li> <li>May explode from friction, shock, heat or containment.</li> <li>Heating may cause expansion or decomposition leading to violent rupture of containers.</li> <li>Heat affected containers remain hazardous.</li> <li>Contact with combustibles such as wood, paper, oil or finely divided metal may produce spontaneous combustion or violent decomposition.</li> <li>May emit irritating, poisonous or corrosive fumes.</li> <li>Combustion/decomposition may produce acrid/toxic fumes of carbon monoxide (CO).</li> </ul>
HAZCHEM	Not Applicable

### **SECTION 6 Accidental release measures**

# Personal precautions, protective equipment and emergency procedures

See section 8

#### **Environmental precautions**

See section 12

### Methods and material for containment and cleaning up

Minor Spills	<ul> <li>Clean up all spills immediately.</li> <li>No smoking, naked lights, ignition sources.</li> <li>Avoid all contact with any organic matter including fuel, solvents, sawdust, paper or cloth and other incompatible materials, as ignition may result.</li> <li>Avoid breathing dust or vapours and all contact with skin and eyes.</li> <li>Control personal contact with the substance, by using protective equipment.</li> <li>Contain and absorb spill with dry sand, earth, inert material or vermiculite.</li> <li>DO NOT use sawdust as fire may result.</li> <li>Scoop up solid residues and seal in labelled drums for disposal.</li> </ul>
Major Spills	<ul> <li>Clear area of personnel and move upwind.</li> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>May be violently or explosively reactive.</li> <li>Wear breathing apparatus and protective gloves.</li> <li>Prevent, by any means available, spillage from entering drains or water courses.</li> <li>No smoking, flames or ignition sources.</li> <li>Increase ventilation.</li> <li>Contain spill with sand, earth or other clean, inert materials.</li> </ul>

Personal Protective Equipment advice is contained in Section 8 of the SDS.

### **SECTION 7 Handling and storage**

Precautions for safe handling	
Safe handling	<ul> <li>For oxidisers, including peroxides.</li> <li>Avoid personal contact and inhalation of dust, mist or vapours.</li> <li>Provide adequate ventilation.</li> <li>Always wear protective equipment and wash off any spillage from clothing.</li> <li>Keep material away from light, heat, flammables or combustibles.</li> <li>Keep cool, dry and away from incompatible materials.</li> <li>Avoid physical damage to containers.</li> <li><b>DO NOT repack or return unused portions to original containers.</b></li> </ul>
Other information	<ul> <li>Store in original containers.</li> <li>Keep containers securely sealed as supplied.</li> <li>Store in a cool, well ventilated area.</li> <li>Keep dry.</li> <li>Store under cover and away from sunlight.</li> <li>Store away from flammable or combustible materials, debris and waste. Contact may cause fire or violent reaction.</li> <li>Store away from incompatible materials and foodstuff containers.</li> </ul>

### Conditions for safe storage, including any incompatibilities

Suitable container	<ul> <li>Metal can or drum</li> <li>Packaging as recommended by manufacturer.</li> <li>Check all containers are clearly labelled and free from leaks.</li> </ul>
Storage incompatibility	<ul> <li>Oxidising agents as a class are not necessarily combustible themselves, but can increase the risk and intensity of fire in many other substances.</li> <li>for metal nitrates: <ul> <li>Segregate from heavy metals, phosphides, sodium acetate, lead nitrate, tartrates, trichloroethylene,</li> <li>Avoid shock and heat.</li> </ul> </li> <li>Mixtures of metal nitrates with alkyl esters may explode due to the formation of unstable alkyl nitrates.</li> <li>Mixtures of a nitrate with phosphorous, tin(II) chloride and other reducing agents may react explosively.</li> <li>Mixtures containing nitrates and organic materials are potentially dangerous, especially if acidic materials or heavy metals are present.</li> <li>Fibrous organic material, jute, wood and similar cellulosic material can become highly combustible by nitrate impregnation</li> <li>Metal nitrates are incompatible with cyanides, thiocyanates, isothiocyanates and hypophosphites. Avoid reaction with the following which can cause an explosion: barium thiocyanate, boron phosphide, cyanides, sodium hypophosphite, sulfur and charcoal, powdered aluminium or aluminium oxide, sodium thiosulfate.</li> <li>Mixtures of metal nitrates and phosphinates may explode on heating</li> <li>A mixture of aluminium powder, water and metal nitrate may explode due to a self accelerating reaction.</li> <li>Mixtures containing nitrates, nitrites and organic materials are potentially dangerous, especially in the presence of acidic materials and heavy metals</li> </ul>

#### **SECTION 8 Exposure controls / personal protection**

#### **Control parameters**

Occupational Exposure Limits (OEL)

### INGREDIENT DATA

Source	Ingredient	Material name		TWA	STEL		Peak	Notes
Australia Exposure Standards	manganese nitrate	Manganese, dust & co	ompounds (as Mn)	1 mg/m3	Not Available		Not Available	Not Available
Emergency Limits								
Ingredient	TEEL-1		TEEL-2			TEEL-3		
manganese nitrate	9.8 mg/m3 16 mg/n		16 mg/m3		96 mg/m3			
manganese nitrate	11 mg/m3	11 mg/m3 18 mg/m3				110 mg/m	3	
Ingredient	Original IDLH	Revised IDL	н					
manganese nitrate	500 mg/m3	500 mg/m3			Not Available			
Distilled Water	Not Available			Not Available				

#### Exposure controls

Appropriate engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" at in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure.         General exhaust is adequate under normal operating conditions.         Eye and face protection       Safety glasses with side shields; or as required.         • Chemical goggles. IASINZS 1337.1, ENI66 or national equivalent]         • Chemical goggles. IASINZS 1337.1, ENI66 or national equivalent]         • Chemical goggles. IASINZS 1337.1, ENI66 or national equivalent]         • Chemical goggles. IASINZS 1337.1, ENI66 or national equivalent]         • Chemical goggles. IASINZS 1337.1, ENI66 or national equivalent]         • Chemical goggles. IASINZS 1337.1, ENI66 or national equivalent]         • Chemical goggles. IASINZS 1337.1, ENI66 or national equivalent]         • Chemical goggles. IASINZS 1337.1, ENI66 or national equivalent]         • Chemical goptin for the class of chemicals in use and an		
Eye and face protection <ul> <li>Safety glasses with side shields; or as required,</li> <li>Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]</li> <li>Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].       See Hand protection below         Hands/feet protection       See Other protection below       Wear chemical protective gloves, e.g. PVC. Wear safety footwear.         Body protection       See Other protection below              <ul> <li>Overalls.</li> <li>Overalls.</li> </ul></li></ul>		be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure.
Eye and face protection <ul> <li>Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]</li> <li>Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irritation - lens should be removed at the first signs of eye redness or irritation - lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].         Skin protection       See Hand protection below         Hands/feet protection       Wear chemical protective gloves, e.g. PVC. Wear safety footwear.         Body protection       See Other protection below         Other protection       &gt; Other protection below</li></ul>	measures, such as personal	
Hands/feet protection       Wear chemical protective gloves, e.g. PVC. Wear safety footwear.         Body protection       See Other protection below         Other protection       • Overalls.	Eye and face protection	<ul> <li>Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]</li> <li>Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in</li> </ul>
Hands/reet protection     Wear safety footwear.       Body protection     See Other protection below       Other protection     Overalls.	Skin protection	See Hand protection below
Other protection • Overalls.	Hands/feet protection	
Other protection	Body protection	See Other protection below
	Other protection	

#### Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

#### "Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the  $\ensuremath{\textit{computer-generated}}$  selection:

Manganese Nitrate 50% solution

Material	СРІ
BUTYL	А
NEOPRENE	А
VITON	А
NATURAL RUBBER	С
PVA	С

\* CPI - Chemwatch Performance Index

#### A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

**NOTE:** As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

#### **Respiratory protection**

Type -P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	-AUS P2	-	-PAPR-AUS / Class 1 P2
up to 50 x ES	-	-AUS / Class 1 P2	-
up to 100 x ES	-	-2 P2	-PAPR-2 P2 ^

#### ^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

### Ansell Glove Selection

Glove — In order of recommendation
AlphaTec 02-100
AlphaTec® Solvex® 37-185
AlphaTec® 38-612
AlphaTec® 58-008
AlphaTec® 58-530B
AlphaTec® 58-530W
AlphaTec® 58-735
AlphaTec® 79-700
AlphaTec® Solvex® 37-675
DermaShield™ 73-711

The suggested gloves for use should be confirmed with the glove supplier.

## **SECTION 9** Physical and chemical properties

### Information on basic physical and chemical properties

Appearance Clear, pink, aqueous solution. No odour. Miscible with water. Concentration 45-55% w/w of the hexahydrate F.Wt. 287.

Physical state	Liquid	Relative density (Water = 1)	1.46-1.92
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	2.0-3.0	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	100 approx.	Molecular weight (g/mol)	178.95 F.Wt.
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	as water	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	as water	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

## **SECTION 10 Stability and reactivity**

Reactivity	See section 7		
Chemical stability	Unstable in the presence of incompatible materials. Unstable under normal storage, requires special storage conditions. Prolonged exposure to heat above control temperature. Presence of shock and/or friction. Hazardous decomposition will occur.		
Possibility of hazardous reactions	ection 7		
Conditions to avoid	e section 7		
Incompatible materials	See section 7		
Hazardous decomposition products	See section 5		

### **SECTION 11 Toxicological information**

### Information on toxicological effects

Inhaled	The liquid is discomforting to the upper respiratory tract and may be harmful if inhaled Manganese fume is toxic and produces nervous system effects characterised by tiredness. Acute poisoning is rare although acute inflammation of the lungs may occur. A chemical pneumonia may also result from frequent exposure. Inhalation of freshly formed metal oxide particles sized below 1.5 microns and generally between 0.02 to 0.05 microns may result in "metal fume fever". Symptoms may be delayed for up to 12 hours and begin with the sudden onset of thirst, and a sweet, metallic or foul taste in the mouth. Other symptoms include upper respiratory tract initiation ecomposition for a durance of the muchan general provide on ecomplication for a durance of the opurer
	irritation accompanied by coughing and a dryness of the mucous membranes, lassitude and a generalised feeling of malaise. Mild to severe

Mutagenicity	× Asp	biration Hazard	×	
Respiratory or Skin sensitisation	× STOT - Repe	ated Exposure	×	
Serious Eye Damage/Irritation	✓ STOT - Si	ngle Exposure	*	
Skin Irritation/Corrosion	✓	Reproductivity	×	
Acute Toxicity	✓ c	arcinogenicity	*	
MANGANESE NITRATE & DISTILLED WATER	No significant acute toxicological data identified in literature search.			
MANGANESE NITRATE	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production. <b>NOTE:</b> Substance has been shown to be mutagenic in at least one assay, or belongs to a family of chemicals producing damage or change to cellular DNA.			
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxi specified data extracted from RTECS - Register of Toxic Effect of chemica		ned from manufacturer's SDS. Unless otherwise	
Distilled Water	TOXICITY           Oral (Rat) LD50: >90000 mg/kg <sup>[2]</sup>	IRRITATION Not Available		
manganese nitrate	Oral (Rat) LD50: >300 mg/kg <sup>[1]</sup> Eye: adverse effect observed (irritating) <sup>[1]</sup> Skin: adverse effect observed (corrosive) <sup>[1]</sup>			
	TOXICITY IRRITATION			
solution	Not Available	Not Available		
Manganese Nitrate 50%	ΤΟΧΙΟΙΤΥ	IRRITATION		
Chronic	Principal routes of exposure are usually by skin contact/eye contact Manganese is an essential trace element. Chronic exposure to low levels of manganese can include a mask-like facial expression, spastic gait, tremors, slurred speech, disordered muscle tone, fatigue, anorexia, loss of strength and energy, apathy and poor concentration.			
Еуе	The material is moderately discomforting to the eyes			
Skin Contact	The material may be mildly discomforting to the skin Prolonged exposure may cause skin reactions Open cuts, abraded or irritated skin should not be exposed to this material Toxic effects may result from skin absorption			
Ingestion	The material is moderately discomforting to the gastro-intestinal tract and may be harmful if swallowed The substance and/or its metabolites may bind to haemoglobin inhibiting normal uptake of oxygen. This condition, known as "methaemoglobinemia", is a form of oxygen starvation (anoxia). Symptoms include cyanosis (a bluish discolouration skin and mucous membranes) and breathing difficulties. Symptoms may not be evident until several hours after exposure. At about 15% concentration of blood methaemoglobin there is observable cyanosis of the lips, nose and earlobes. Symptoms may be absent although euphoria, flushed face and headache are commonly experienced. At 25-40%, cyanosis is marked but little disability occurs other than that produced on physical exertion. At 40-60%, symptoms include weakness, dizziness, lightheadedness, increasingly severe headache, ataxia, rapid shallow respiration, drowsiness, nausea, vomiting, confusion, lethargy and stupor. Manganese is an essential trace element. Chronic exposure to low levels of manganese can include a mask-like facial expression, spastic gait, tremors, slurred speech, disordered muscle tone, fatigue, anorexia, loss of strength and energy, apathy and poor concentration.			
	headache, nausea, occasional vomiting, fever or chills, exaggerated mental activity, profuse sweating, diarrhoea, excessive urination and prostration may also occur. Tolerance to the fumes develops rapidly, but is quickly lost. Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled. If prior damage to the circulatory or nervous systems has occurred or if kidney damage has been sustained, proper screenings should be conducted on individuals who may be exposed to further risk if handling and use of the material result in excessive exposures.			

Data either not available or does not till the crit
 Data available to make classification

## **SECTION 12 Ecological information**

Endpoint	Test Duration (hr)	Species	Species		Source
Not Available	Not Available	Not Available	Not Available Not Available		Not Available
Endpoint	Test Duration (hr)	Species	Valu	ie	Source
EC50	72h	Algae or other aquatic plants	gae or other aquatic plants 61mg/l		2
EC50	48h	Crustacea	Crustacea 0.8mg/l		2
LC50	96h	Fish	>=2	.4<=17.4mg/l	2
NOEC(ECx)	1440h	Crustacea	0.01	mg/l	2
Endpoint	Test Duration (hr)	Species		Value	Source
Not Available	Not Available	Not Available		Not Available	Not Available
	Not Available EC50 EC50 LC50 NOEC(ECx) Endpoint Not	Not AvailableNot AvailableEndpointTest Duration (hr)EC5072hEC5048hLC5096hNOEC(ECx)1440hEndpointTest Duration (hr)NotNot Available	Not Available     Not Available     Not Available       Endpoint     Test Duration (hr)     Species       EC50     72h     Algae or other aquatic plants       EC50     48h     Crustacea       LC50     96h     Fish       NOEC(ECx)     1440h     Crustacea       Endpoint     Test Duration (hr)     Species       Not     Not Available     Not Available	Not Available     Not Available     Not Available       Endpoint     Test Duration (hr)     Species     Value       EC50     72h     Algae or other aquatic plants     61m       EC50     48h     Crustacea     0.8m       LC50     96h     Fish     >=2       NOEC(ECx)     1440h     Crustacea     0.01       Endpoint     Test Duration (hr)     Species       Not     Not Available     Not Available	Not Available     Not Available     Not Available     Not Available       Endpoint     Test Duration (hr)     Species     Value       EC50     72h     Algae or other aquatic plants     61mg/l       EC50     48h     Crustacea     0.8mg/l       LC50     96h     Fish     >=2.4<=17.4mg/l

#### DO NOT discharge into sewer or waterways.

#### Persistence and degradability

Ingredient	Persistence: Water/Soil Persistence: Air		
Distilled Water	LOW LOW		
Bioaccumulative potential			
Ingredient	Bioaccumulation		
	No Data available for all ingredients		
Mobility in soil			
Ingredient	Mobility		
	No Data available for all ingredients		

#### **SECTION 13 Disposal considerations**

Waste treatment methods	
Product / Packaging disposal	<ul> <li>For small quantities: Dissolve in 1. water or 2. acid solution or 3. oxidise to water soluble state. Precipitate the material as the sulfide and adjust the pH to 7 to complete precipitation. Dispose of filtered solids. Destroy excess sulfide with sodium hypochlorite. Neutralise and flush to sewer (local regulation permitting).</li> <li>Recycle wherever possible. Special hazard may exist - specialist advice may be required.</li> <li>Consult manufacturer for recycling options.</li> <li>Consult State Land Waste Management Authority for disposal.</li> <li>Bury or incinerate residue at an approved site.</li> <li>Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.</li> <li>Puncture containers to prevent re-use and bury at an authorised landfill.</li> </ul>

### **SECTION 14 Transport information**

Labels Required		
Marine Pollutant	NO	
HAZCHEM	Not Applicable	

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

# 14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

#### 14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
manganese nitrate	Not Available
Distilled Water	Not Available

### 14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
manganese nitrate	Not Available

Product name Ship Type Distilled Water Not Available

#### **SECTION 15 Regulatory information**

#### Safety, health and environmental regulations / legislation specific for the substance or mixture

# manganese nitrate is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals Australian Inventory of Industrial Chemicals (AIIC)

# Distilled Water is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

### Additional Regulatory Information

Not Applicable

### **National Inventory Status**

National Inventory	Status		
Australia - AIIC / Australia Non-Industrial Use	Yes		
Canada - DSL	/es		
Canada - NDSL	No (manganese nitrate; Distilled Water)		
China - IECSC	es		
Europe - EINEC / ELINCS / NLP			
Japan - ENCS			
Korea - KECI	5		
New Zealand - NZIoC	es		
Philippines - PICCS	Yes		
USA - TSCA	Yes		
Taiwan - TCSI	Yes		
Mexico - INSQ	Yes		
Vietnam - NCI	Yes		
Russia - FBEPH	Yes		
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.		

#### **SECTION 16 Other information**

Revision Date	23/12/2022
Initial Date	28/09/2001

#### SDS Version Summary

Version	Date of Update	Sections Updated
4.1	01/11/2019	One-off system update. NOTE: This may or may not change the GHS classification
5.1	23/12/2022	Classification review due to GHS Revision change.

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

#### Definitions and abbreviations

- PC TWA: Permissible Concentration-Time Weighted Average
- PC STEL: Permissible Concentration-Short Term Exposure Limit
- IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists
- STEL: Short Term Exposure Limit
- TEEL: Temporary Emergency Exposure Limit,
- IDLH: Immediately Dangerous to Life or Health Concentrations Þ
- ES: Exposure Standard
- OSF: Odour Safety Factor
- NOAEL: No Observed Adverse Effect Level ۲
- LOAEL: Lowest Observed Adverse Effect Level ۶
- TLV: Threshold Limit Value Þ
- LOD: Limit Of Detection
- OTV: Odour Threshold Value BCF: BioConcentration Factors ÷.
- BEI: Biological Exposure Index

end of SDS

### Manganese Nitrate 50% solution

- DNEL: Derived No-Effect Level
- PNEC: Predicted no-effect concentration
- AIIC: Australian Inventory of Industrial Chemicals
- DSL: Domestic Substances List
- NDSL: Non-Domestic Substances List
- ► IECSC: Inventory of Existing Chemical Substance in China
- EINECS: European INventory of Existing Commercial chemical Substances
   ELINCS: European List of Notified Chemical Substances
- NLP: No-Longer Polymers
- ENCS: Existing and New Chemical Substances Inventory ۲

- ENCS: Existing and New Orientical Substances inventory
   KECI: Korea Existing Chemicals Inventory
   NZIoC: New Zealand Inventory of Chemicals
   PICCS: Philippine Inventory of Chemicals and Chemical Substances
- ۲ TSCA: Toxic Substances Control Act
- TCSI: Taiwan Chemical Substance Inventory
- INSQ: Inventario Nacional de Sustancias Químicas
- NCI: National Chemical Inventory
- FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

#### This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.