

Metalstrip corrector 1860

ADDITIVE FOR FASTRIP PAINT-STRIPPER

Metalstrip Corrector 1860 Is a quick-acting delacquering additive especially developed for inline chemical stripping applications. Metalstrip Corrector 1860 is added "as-is" in Metalstrip 1460 Fastrip dipping plants and it is free from halogenated hydrocarbons.

Density	about 1,03 g/ml Metalstrip Corrector 1860
Temperature	40 – 70°C
Dosage	About 5% to 30% According to our technical service (see maintaining concentration)
Form of delivery	Metalstrip corrector 1860 25 KG (Jerrican)

The action of the product is strongly influenced by the lacquer layer thickness. Therefore, the optimal operational parameters may lie outside the indicated standard areas in individual cases.

Safety precautions Please comply with all chemical handling regulations. Please refer to the Safety Data Sheet for information about product transport, storage, handling, and further details. Use appropriate personal protective equipment while using and handling the product. Avoid contact and inhalation. If the product comes into contact with the skin or eyes, wash thoroughly with water and consult a doctor.

Tank material A suitable tank material is iron or steel, preferably stainless steel. Tanks of zinc, galvanized steel or aluminum must not be used.

Maintaining concentration Metalstrip Corrector is a specific additive developed in order to improve the stripping performances, especially after the filtration process on Metalstrip 1460 Fastrip plants. The dosage (about 5% to 30%) must be agreed with the Alit-Tecnologies technical service.

We will be happy to provide you with our knowledge and advice to guarantee the best process quality.