

BARIUM SULPHATE ALPHA CHEMICALS PTY LTD

Chemwatch Hazard Alert Code: 1

Issue Date: **20/06/2022** Print Date: **06/02/2023** S.GHS.AUS.EN

Chemwatch: 13887
Version No: 6.1
Safety Data Sheet according to WHS Regulations (Hazardous Chemicals) Amendment 2020 and ADG requirements

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

1 Toddot Identifier	
Product name	BARIUM SULPHATE
Chemical Name	barium sulfate
Synonyms	Ba-O4-S; BaSO4; BaO4S; C.I. 77120; barium sulphate; precipitated barium sulfate 1:1; barytes; barite; sulfuric sulphuric acid barium salt 1:1; precipitated barytes; heavy spar; Actybaryte Finemeal Barium Sulfuricium; Barii Sulphas Sulfas Blank-fixe; Bakontal Intestibar Minbar 70 Medebar 85 Medescan; Baridol Lactobaryt Minbar 80 Medebar M Tixobar; Baritop Liquibarine Minbar 90 Medebar Plus Medebar XAC_90; Barosperse Macropaque Barotrast Micropaque; Baryta White Neobarst Barytes 22 Oratrast; Basofor Raybar Redi-Flow; Citobaryum Solbar Colonatrast Supramike; Enamel White Travad Esophotrast Unibaryt; C.I. Pigment White 21 Eweiss; Permanent White E-z-paque; Barytes 22; Barimite UF, XF, G-50; Cimbarto; CAS RN: 13462-86-7 - natural barium sulfate; Barium Sulphate for Soil Analysis; Minbar 80; Blanc fixe; Minbar Barytes
Chemical formula	Ba .H2-O4-S Ba.H2O4S O4-S.Ba
Other means of identification	Not Available
CAS number	7727-43-7

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Occurs naturally as mineral barite, barytes. Wide use as inert filler pigment extender in paints, primers, inks, plastics, floor tiles, paper coatings, polymer fibres and rubber. Used as the semi transparent base (lake) for organic pigments. Used as a thixotropic weighting mud in oil well drilling. Barium sulfate is radio-opaque and is used as barium meal in medical X ray diagnosis. CARE: in dispensing, barium sulfate must be named in full to avoid confusion with poisonous barium sulfide, sulfite or carbonate. The raw material for manufacture of lithopone, a white pigment; In the manufacture of photographic paper, wallpaper and glassmaking. In battery plate expanders; in heavy concrete for radiation shield.

Details of the manufacturer or supplier of the safety data sheet

	Triple and the second s	
Registered company name	ALPHA CHEMICALS PTY LTD	
Address	4 ALLEN PLACE WETHERILL PARK NSW 2164 Australia	
Telephone	61 (0)2 9982 4622	
Fax	Not Available	
Website	Website ~	
Email	shane@alphachem.com.au	

Emergency telephone number

Association / Organisation	ALPHA CHEMICALS PTY LTD	CHEMWATCH EMERGENCY RESPONSE	
Emergency telephone numbers	61 (0)418 237 771	+61 1800 951 288	
Other emergency telephone numbers	Not Available	+61 3 9573 3188	

Once connected and if the message is not in your preferred language then please dial 01

SECTION 2 Hazards identification

Classification of the substance or mixture

NON-HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

Chemwatch Hazard Ratings

	Min	Max	
Flammability	0		
Toxicity	0		0 = Minimum
Body Contact	1		1 = Low
Reactivity	0		2 = Moderate
Chronic	0		3 = High 4 = Extreme

Poisons Schedule Not Applicable

Issue Date: 20/06/2022 Print Date: 06/02/2023

Classification [1] Not Applicable Label elements Hazard pictogram(s) Not Applicable

Hazard statement(s)

Not Applicable

Precautionary statement(s) Prevention

Signal word

Not Applicable

Precautionary statement(s) Response

Not Applicable

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Not Applicable

SECTION 3 Composition / information on ingredients

Not Applicable

Substances

CAS No	%[weight]	Name
7727-43-7	99.95	Barium Sulphate

Legend:

1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L;

* EU IOELVs available

Mixtures

See section above for composition of Substances

SECTION 4 First aid measures

Description of first aid measures

Eye Contact	If this product comes in contact with eyes: Wash out immediately with water. If irritation continues, seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin or hair contact occurs: ► Flush skin and hair with running water (and soap if available). ► Seek medical attention in event of irritation.
Inhalation	 If dust is inhaled, remove from contaminated area. Encourage patient to blow nose to ensure clear passage of breathing. If irritation or discomfort persists seek medical attention.
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

Extinguishing media

- ▶ There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

- p	pools, iis=si ao siiioiig iioiii ailo osaonsio o' iiiiisisi		
Fire Incompatibility None known.			
Advice for firefighters			
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire. Prevent, by any means available, spillage from entering drains or water courses. Use fire fighting procedures suitable for surrounding area. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. Equipment should be thoroughly decontaminated after use. 		
	Non combustible. Not considered a significant fire risk, however containers may burn.		

Fire/Explosion Hazard

Decomposition may produce toxic fumes of:

sulfur oxides (SOx)

 Chemwatch: 13887
 Page 3 of 8
 Issue Date: 20/06/2022

 Version No: 6.1
 BARIUM SULPHATE
 Print Date: 06/02/2023

	metal oxides May emit poisonous fumes. May emit corrosive fumes.
HAZCHEM	Not Applicable

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills

Major Spills

► Clean up all spills immediately.

Avoid breathing dust and contact with skin and eyes.

Wear protective clothing, gloves, safety glasses and dust respirator.
 Use dry clean up procedures and avoid generating dust.

► Sweep up, shovel up or

▶ Vacuum up (consider explosion-proof machines designed to be grounded during storage and use).

▶ Place spilled material in clean, dry, sealable, labelled container.

Moderate hazard.

CAUTION: Advise personnel in area.

Alert Emergency Services and tell them location and nature of hazard.

Control personal contact by wearing protective clothing.

Prevent, by any means available, spillage from entering drains or water courses.

► Recover product wherever possible.

• IF DRY: Use dry clean up procedures and avoid generating dust. Collect residues and place in sealed plastic bags or other containers for disposal.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- ▶ DO NOT allow material to contact humans, exposed food or food utensils.
- Avoid contact with incompatible materials.
- When handling, **DO NOT** eat, drink or smoke.

Other information

Safe handling

- ► Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- ▶ Observe manufacturer's storage and handling recommendations contained within this SDS.

Conditions for safe storage, including any incompatibilities

Suitable container

- Glass container is suitable for laboratory quantities
- ► Polyethylene or polypropylene container.
- Check all containers are clearly labelled and free from leaks.

Storage incompatibility

- ▶ Metals and their oxides or salts may react violently with chlorine trifluoride and bromine trifluoride.
- These trifluorides are hypergolic oxidisers. They ignite on contact (without external source of heat or ignition) with recognised fuels contact with these materials, following an ambient or slightly elevated temperature, is often violent and may produce ignition.
- ► The state of subdivision may affect the results.

Barium sulfate (barytes)

- reacts violently with dimethyl sulfoxide, sodium acetylide, finely divided carbon, aluminium, magnesium, zirconium, and possibly other active metals, especially at elevated temperatures
- b is incompatible with potassium, phosphorus (ignites when primed with nitrate-calcium silicide)

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	Barium Sulphate	Barium sulphate	10 mg/m3	Not Available	Not Available	(a) This value is for inhalable dust containing no asbestos and < 1% crystalline silica.

Chemwatch: 13887 Version No: 6.1 Page 4 of 8

BARIUM SULPHATE

Issue Date: 20/06/2022 Print Date: 06/02/2023

Ingredient	TEEL-1	TEEL-2		TEEL-3
Barium Sulphate	15 mg/m3	170 mg/m3		990 mg/m3
Ingredient	Original IDLH		Revised IDLH	
Barium Sulphate	Not Available	Not Available		

Exposure controls

Dust is very dense and settles quickly.

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.

Employers may need to use multiple types of controls to prevent employee overexposure.

Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction.

Personal protection

Appropriate engineering

controls









- Safety glasses with side shields.
- Chemical goggles.

Eye and face protection

Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly.

Skin protection

See Hand protection below

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

Hands/feet protection

Suitability and durability of glove type is dependent on usage

Experience indicates that the following polymers are suitable as glove materials for protection against undissolved, dry solids, where abrasive particles are not present.

- polychloroprene.
- nitrile rubber
- butyl rubber.
- ► fluorocaoutchouc
- polyvinyl chloride

Gloves should be examined for wear and/ or degradation constantly.

Body protection

See Other protection below

Other protection

- Overalls.P.V.C apron.
- Barrier cream.
- Barrier cream.
 Skin cleansing cream.
- Eye wash unit.

Respiratory protection

Type -P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	P1 Air-line*	-	PAPR-P1
up to 50 x ES	Air-line**	P2	PAPR-P2
up to 100 x ES	-	P3	-
		Air-line*	-
100+ x ES	-	Air-line**	PAPR-P3

* - Negative pressure demand ** - Continuous flow

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- · Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.
- The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).
- Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.
- · Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.
- · Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN143) dust masks. Use respirators and components tested and approved under

BARIUM SULPHATE

Issue Date: 20/06/2022 Print Date: 06/02/2023

appropriate government standards such as NIOSH (US) or CEN (EU)

- · Use approved positive flow mask if significant quantities of dust becomes airborne.
- · Try to avoid creating dust conditions.

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

	Dense fine odourless white powder or polymorphous crystals. Solubility in water 0.00025% i.e. practically insoluble. Only 0.6% solubility in 3%
Appearance	hydrochloric acid solution. Slightly soluble in concentrated sulfuric acid and soluble in hot concentrated sulfuric acid. Particle size 2-25 microns.
	Rhombic crystals with a transition point at 1149 deg C to monoclinic. Finer grades, are precipitated.

The more of years man a management at the dog of the more small and prosperation.		
Divided Solid	Relative density (Water = 1)	4.5 @ 15 C
Not Available	Partition coefficient n-octanol / water	Not Available
Not Available	Auto-ignition temperature (°C)	Not Applicable
Not Applicable	Decomposition temperature (°C)	> 1600
1580	Viscosity (cSt)	Not Applicable
Not Available	Molecular weight (g/mol)	233.39
Not Applicable	Taste	Not Available
Non Volatile	Explosive properties	Not Available
Not Applicable	Oxidising properties	Not Available
Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Applicable
Not Applicable	Volatile Component (%vol)	Nil
Negligible	Gas group	Not Available
Immiscible	pH as a solution (1%)	Not Applicable
Not Applicable	VOC g/L	Not Available
	Divided Solid Not Available Not Available Not Applicable 1580 Not Available Not Applicable Individual of the properties of the pr	Divided Solid Relative density (Water = 1) Not Available Not Available Not Applicable Not Applicable Not Available Not Applicable Not Available Not Available Not Available Not Available Not Available Not Applicable Pl as a solution (1%)

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological ef	fects
Inhaled	There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled. If prior damage to the circulatory or nervous systems has occurred or if kidney damage has been sustained, proper screenings should be conducted on individuals who may be exposed to further risk if handling and use of the material result in excessive exposures. Not normally a hazard due to non-volatile nature of product Barium furnes are respiratory irritants. Over-exposure to barium dusts and furne may result in rhinitis, frontal headache, wheezing, laryngeal spasm, salivation and anorexia. Long term effects include nervous disorders and adverse effects on the heart, circulatory system and musculature. Heavy exposures may result in a benign pneumoconiosis.
Ingestion	Sulfates are not well absorbed orally, but can cause diarrhoea. The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
Skin Contact	The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may cause transient discomfort characterised by tearing or conjunctival redness (as with windburn). Slight abrasive damage may also result.
Chronic	Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. Long term exposure to high dust concentrations may cause changes in lung function i.e. pneumoconiosis, caused by particles less than 0.5 micron penetrating and remaining in the lung. Barium compounds may cause high blood pressure, airway irritation and damage the liver, spleen and bone marrow. Prolonged exposure may

BARIUM SULPHATE

Issue Date: **20/06/2022**Print Date: **06/02/2023**

	cause a lung inflammation and scarring.		
	TOXICITY	IRRITATION	
Barium Sulphate	dermal (rat) LD50: >2000 mg/kg ^[1] Oral (Mouse) LD50; >3000 mg/kg ^[2]	Not Available	
Legend:	Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances		
BARIUM SULPHATE	No significant acute toxicological data identified in liter	rature search.	
Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	×	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

Legend:

💢 – Data either not available or does not fill the criteria for classification

Data available to make classification

SECTION 12 Ecological information

Toxicity

	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	72h	Algae or other aquatic plants	>=1.15mg/l	2
Barium Sulphate	EC50	72h	Algae or other aquatic plants	>1.15mg/l	2
	LC50	96h	Fish	>3.5mg/l	2
	EC50	48h	Crustacea	32mg/l	2
Legend:	Ecotox database	. IUCLID Toxicity Data 2. Europe ECHA Register a - Aquatic Toxicity Data 5. ECETOC Aquatic Haz on Data 8. Vendor Data	•		

For Inorganic Sulfate:

Environmental Fate - Sulfates can produce a laxative effect at concentrations of 1000 - 1200 mg/liter, but no increase in diarrhea, dehydration or weight loss. The presence of sulfate in drinking-water can also result in a noticeable taste. Sulfate may also contribute to the corrosion of distribution systems. No health-based guideline value for sulfate in drinking water is proposed.

Atmospheric Fate: Sulfates are removed from the air by both dry and wet deposition processes. Wet deposition processes including rain-out (a process that occurs within the clouds) and washout (removal by precipitation below the clouds) which contribute to the removal of sulfate from the atmosphere.

Terrestrial Fate: Soil - In soil, the inorganic sulfates can adsorb to soil particles or leach into surface water and groundwater. Plants - Sodium sulfate is not very toxic to terrestrial plants however; sulfates can be taken up by plants and be incorporated into the parenchyma of the plant.

For Barium and its Compounds:

Environmental Fate: Barium is a highly reactive metal occurring naturally only in a combined state, primarily as inorganic complexes. Conditions such as pH, oxidation-reduction potential, cation exchange capacity, and the presence of sulfate, carbonate, and the presence of metal oxides will affect the partitioning of barium and its compounds in the environment. The element is released to environmental by both natural processes and man-made sources. Most barium released to the environment from industrial sources is in forms that do not become widely dispersed.

Atmospheric Fate: In the atmosphere, barium is likely to be present in particulate form. Barium compounds will be removed from the atmosphere via wet/dry deposition. The substance may change to different forms of barium in the air.

Terrestrial Fate: Soil - Barium will leach from geological formations to groundwater and will adsorb to soil.

DO NOT discharge into sewer or waterways

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

Bioaccumulative potential

Ingredient	Bioaccumulation
	No Data available for all ingredients

Mobility in soil

Ingredient	Mobility	
	No Data available for all ingredients	

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

Reduction

BARIUM SULPHATE

Issue Date: **20/06/2022**Print Date: **06/02/2023**

- ► Reuse
- Recycling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate. In most instances the supplier of the material should be consulted.

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- ▶ Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Management Authority for disposal.
- ▶ Bury residue in an authorised landfill.
- ▶ Recycle containers if possible, or dispose of in an authorised landfill.

SECTION 14 Transport information

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
Barium Sulphate	Not Available

Transport in bulk in accordance with the ICG Code

Product name	Ship Type
Barium Sulphate	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

Barium Sulphate is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (Barium Sulphate)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	20/06/2022
Initial Date	16/06/2005

Page 8 of 8 BARIUM SULPHATE

Issue Date: 20/06/2022 Print Date: 06/02/2023

Version	Date of Update	Sections Updated
4.1	17/05/2007	Acute Health (eye), Acute Health (inhaled), Acute Health (skin), Acute Health (swallowed), CAS Number, Chronic Health, Disposal, Engineering Control, Environmental, Exposure Standard, Fire Fighter (extinguishing media), Fire Fighter (fire/explosion hazard), Fire Fighter (fire incompatibility), First Aid (skin), Handling Procedure, Instability Condition, Personal Protection (other), Personal Protection (eye), Personal Protection (hands/feet), Physical Properties, Spills (major), Spills (minor), Storage (storage incompatibility), Storage (suitable container), Supplier Information, Synonyms, Toxicity and Irritation (Other)
6.1	20/06/2022	Expiration. Review and Update

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

ES: Exposure Standard

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index

AIIC: Australian Inventory of Industrial Chemicals

DSL: Domestic Substances List

NDSL: Non-Domestic Substances List

IECSC: Inventory of Existing Chemical Substance in China

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

NLP: No-Longer Polymers

ENCS: Existing and New Chemical Substances Inventory

KECI: Korea Existing Chemicals Inventory

NZIoC: New Zealand Inventory of Chemicals

PICCS: Philippine Inventory of Chemicals and Chemical Substances

TSCA: Toxic Substances Control Act

TCSI: Taiwan Chemical Substance Inventory

INSQ: Inventario Nacional de Sustancias Químicas

NCI: National Chemical Inventory

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.