

ALPHA CHEMICALS PTY LTD

Chemwatch Hazard Alert Code: 2

Chemwatch: 18383

Version No: 8.1 Safety Data Sheet according to Work Health and Safety Regulations (Hazardous Chemicals) 2023 and ADG requirements Issue Date: **15/04/2021** Print Date: **07/11/2024** S.GHS.AUS.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

| Product name | ISO-AMYL ALCOHOL | |
|-------------------------------|---|--|
| Chemical Name | Not Available | |
| Synonyms | C5-H12-O; C5-H11-OH; CH3CH(CH3)CH2CH2OH; primary isoamyl alcohol; iso-pentylalcohol; isopentyl alcohol; 3-methyl-1-butanol; isoamyl alcohol; isobutyl carbinol; fermentation amyl alcohol; 3-methyl butanol; 3-methyl-butan-1-ol; isoamyl alcohol, kosher | |
| Proper shipping name | PENTANOLS | |
| Chemical formula | (CH3)2CHCH2CH2OH | |
| Other means of identification | Not Available | |
| CAS number | 123-51-3 | |

Relevant identified uses of the substance or mixture and uses advised against

| Relevant identified uses | Used as a solvent for fats, resins, alkaloids and in lacquers; in the manufacture of isoamyl compounds, isovaleric acid, mercury fulminate, artificial silk, smokeless powders; in microscopy and determining milk fat. Solvent. In perfumery/ flavouring. |
|--------------------------|---|
|--------------------------|---|

Details of the manufacturer or supplier of the safety data sheet

| Registered company name | ALPHA CHEMICALS PTY LTD | |
|-------------------------|---|--|
| Address | 4 ALLEN PLACE WETHERILL PARK NSW 2164 Australia | |
| Telephone | 61 (0)2 9982 4622 | |
| Fax | Not Available | |
| Website | ~ | |
| Email | shane@alphachem.com.au | |

Emergency telephone number

| Association / Organisation | ALPHA CHEMICALS PTY LTD | CHEMWATCH EMERGENCY RESPONSE (24/7) |
|--|-------------------------|-------------------------------------|
| Emergency telephone number(s) | 61 (0)418 237 771 | +61 1800 951 288 |
| Other emergency telephone number(s) | Not Available | +61 3 9573 3188 |

Once connected and if the message is not in your preferred language then please dial 01

SECTION 2 Hazards identification

Classification of the substance or mixture

HAZARDOUS CHEMICAL. DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

Chemwatch Hazard Ratings

| | Min | Max | |
|--------------|-----|-----|-------------------------|
| Flammability | 2 | | |
| Toxicity | 2 | | 0 = Minimum |
| Body Contact | 2 | | 1 = Low |
| Reactivity | 1 | | 2 = Moderate |
| Chronic | 0 | | 3 = High 4 = Extreme |

| Poisons Schedule | Not Applicable | |
|-------------------------------|--|--|
| Classification ^[1] | Flammable Liquids Category 3, Acute Toxicity (Oral) Category 4, Serious Eye Damage/Eye Irritation Category 2B, Acute Toxicity (Inhalation) Category 4, Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3 | |
| Legend: | 1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI | |

| Hazard pictogram(s) | |
|---------------------|--|
| | |

Warning

Signal word

Hazard statement(s)

| nazura oracomoni(o) | | |
|---------------------|--|--|
| H226 | Flammable liquid and vapour. | |
| H302 | Harmful if swallowed. | |
| H320 | Causes eye irritation. | |
| H332 | Harmful if inhaled. | |
| H335 | May cause respiratory irritation. | |
| AUH019 | May form explosive peroxides. | |
| AUH066 | Repeated exposure may cause skin dryness and cracking. | |

Precautionary statement(s) Prevention

| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. | |
|------|--|--|
| P271 | Use only outdoors or in a well-ventilated area. | |
| P240 | Ground and bond container and receiving equipment. | |
| P241 | Use explosion-proof electrical/ventilating/lighting/intrinsically safe equipment. | |
| P242 | Use non-sparking tools. | |
| P243 | P243 Take action to prevent static discharges. | |
| P261 | P261 Avoid breathing mist/vapours/spray. | |
| P264 | Wash all exposed external body areas thoroughly after handling. | |

Precautionary statement(s) Response

| P370+P378 | In case of fire: Use alcohol resistant foam or normal protein foam to extinguish. | |
|----------------|--|--|
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. | |
| P337+P313 | f eye irritation persists: Get medical advice/attention. | |
| P301+P312 | IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider if you feel unwell. | |
| P303+P361+P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. | |
| P304+P340 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. | |
| P330 | Rinse mouth. | |

Precautionary statement(s) Storage

| P403+P235 | Store in a well-ventilated place. Keep cool. |
|-----------|--|
| P405 | Store locked up. |

Precautionary statement(s) Disposal

P501

Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

| CAS No | | %[weight] | Name |
|----------|--|-----------|------------------|
| 123-51-3 | | >97 | iso-amyl alcohol |
| Legend: | 1. Classified by Chernwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available | | |

Mixtures

See section above for composition of Substances

SECTION 4 First aid measures

| Descri | ption | of first | aid | measures | |
|--------|-------|----------|-----|----------|--|
| | | | | | |

| Eye Contact | If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. | | | | |
|--------------|---|--|--|--|--|
| Skin Contact | If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation. | | | | |
| Inhalation | If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. | | | | |

| | Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay. |
|-----------|---|
| Ingestion | If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice. Avoid giving milk or oils. Avoid giving alcohol. If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus. |

Indication of any immediate medical attention and special treatment needed

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.

- To treat poisoning by the higher aliphatic alcohols (up to C7): Gastric lavage with copious amounts of water.
- It may be beneficial to instill 60 ml of mineral oil into the stomach.
- Oxygen and artificial respiration as needed.
- Electrolyte balance: it may be useful to start 500 ml. M/6 sodium bicarbonate intravenously but maintain a cautious and conservative attitude toward electrolyte replacement unless shock or severe acidosis threatens.
- To protect the liver, maintain carbohydrate intake by intravenous infusions of glucose.
- + Haemodialysis if coma is deep and persistent. [GOSSELIN, SMITH HODGE: Clinical Toxicology of Commercial Products, Ed 5)

BASIC TREATMENT

- Establish a patent airway with suction where necessary.
- Watch for signs of respiratory insufficiency and assist ventilation as necessary. Administer oxygen by non-rebreather mask at 10 to 15 l/min
- Monitor and treat, where necessary, for shock
- Monitor and treat, where necessary, for pulmonary oedema. Anticipate and treat, where necessary, for seizures
- DO NOT use emetics. Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.Give activated charcoal.

ADVANCED TREATMENT

- Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- Positive-pressure ventilation using a bag-valve mask might be of use.
- Monitor and treat, where necessary, for arrhythmias.
- Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- If the patient is hypoglycaemic (decreased or loss of consciousness, tachycardia, pallor, dilated pupils, diaphoresis and/or dextrose strip or glucometer readings below 50 mg), give 50% dextrose.
- Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema
- Treat seizures with diazepam.
- Proparacaine hydrochloride should be used to assist eye irrigation.

EMERGENCY DEPARTMENT

- Laboratory analysis of complete blood count, serum electrolytes, BUN, creatinine, glucose, urinalysis, baseline for serum aminotransferases (ALT and AST), calcium. phosphorus and magnesium, may assist in establishing a treatment regime. Other useful analyses include anion and osmolar gaps, arterial blood gases (ABGs), chest radiographs and electrocardiograph.
- Positive end-expiratory pressure (PEEP)-assisted ventilation may be required for acute parenchymal injury or adult respiratory distress syndrome.
- Acidosis may respond to hyperventilation and bicarbonate therapy.
- Haemodialysis might be considered in patients with severe intoxication.
- Consult a toxicologist as necessary. BRONSTEIN, A.C. and CURRANCE, P.L. EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

For C8 alcohols and above.

Symptomatic and supportive therapy is advised in managing patients.

SECTION 5 Firefighting measures

Extinguishing media

- Alcohol stable foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog Large fires only.

Special hazards arising from the substrate or mixture

| Fire Incompatibility | Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result |
|-------------------------|--|
| Advice for firefighters | |
| Fire Fighting | Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course. If safe, switch off electrical equipment until vapour fire hazard removed. Use water delivered as a fine spray to control fire and cool adjacent area. Avoid spraying water onto liquid pools. DO NOT approach containers suspected to be hot. |

| Fire/Explosion Hazard | Liquid and vapour are flammable. Moderate fire hazard when exposed to heat or flame. Vapour forms an explosive mixture with air. Moderate explosion hazard when exposed to heat or flame. Vapour may travel a considerable distance to source of ignition. Heating may cause expansion or decomposition leading to violent rupture of containers. On combustion, may emit toxic fumes of carbon monoxide (CO). Combustion products include: carbon monoxide (CO) carbon dioxide (CO2) other pyrolysis products typical of burning organic material. WARNING: Long standing in contact with air and light may result in the formation of potentially explosive peroxides. |
|-----------------------|---|
| HAZCHEM | •3Y |

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

| Minor Spills | Remove all ignition sources. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb small quantities with vermiculite or other absorbent material. Wipe up. Collect residues in a flammable waste container. |
|--------------|--|
| Major Spills | Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course. No smoking, naked lights or ignition sources. Increase ventilation. Stop leak if safe to do so. |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

| Precautions for safe handling | |
|-------------------------------|--|
| Safe handling | Containers, even those that have been emptied, may contain explosive vapours. Do NOT cut, drill, grind, weld or perform similar operations on or near containers. DO NOT allow clothing wet with material to stay in contact with skin The substance accumulates peroxides which may become hazardous only if it evaporates or is distilled or otherwise treated to concentrate the peroxides. The substance may concentrate around the container opening for example. Purchases of peroxidisable chemicals should be restricted to ensure that the chemical is used completely before it can become peroxidised. A responsible person should maintain an inventory of peroxidisable chemicals or annotate the general chemical inventory to indicate which chemicals are subject to peroxidation. An expiration date should be determined. The chemical should either be treated to remove peroxides or disposed of before this date. The person or laboratory receiving the chemical should record a receipt date on the bottle. The individual opening the container should add an opening date. Avoid all personal contact, including inhalation. Wear protective clothing when risk of overexposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. DO NOT enter confined spaces until atmosphere has been checked. Avoid generation of static electricity. DO NOT use plastic buckets. |
| Other information | Store in original containers in approved flammable liquid storage area. Store away from incompatible materials in a cool, dry, well-ventilated area. DO NOT store in pits, depressions, basements or areas where vapours may be trapped. No smoking, naked lights, heat or ignition sources. Storage areas should be clearly identified, well illuminated, clear of obstruction and accessible only to trained and authorised personnel - adequate security must be provided so that unauthorised personnel do not have access. Store according to applicable regulations for flammable materials for storage tanks, containers, piping, buildings, rooms, cabinets, allowable quantities and minimum storage distances. Use non-sparking ventilation systems, approved explosion proof equipment and intrinsically safe electrical systems. Have appropriate extinguishing capability in storage area (e.g. portable fire extinguishers - dry chemical, foam or carbon dioxide) and flammable gas detectors. |

Conditions for safe storage, including any incompatibilities

Suitable container

| • | Packing | as sup | plied by | manufacturer. |
|---|---------|--------|----------|---------------|
| | | | | |

- Plastic containers may only be used if approved for flammable liquid.
- Check that containers are clearly labelled and free from leaks.
- For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.For materials with a viscosity of at least 2680 cSt. (23 deg. C)

 - For manufactured product having a viscosity of at least 250 cSt. (23 deg. C)

Manufactured product that requires stirring before use and having a viscosity of at least 20 cSt (25 deg. C): (i) Removable head packaging; (ii) Cans with friction closures and (iii) low pressure tubes and cartridges may be used.

| | Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with inner and outer packages In addition, where inner packagings are glass and contain liquids of packing group I there must be sufficient inert absorbent to absorb any spillage, unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic. |
|-------------------------|---|
| Storage incompatibility | Isoamyl alcohol: reacts violently with strong oxidisers reacts violently with aliphatic amines, alkalis, ammonium persulfate, boranes, bromine dioxide, isocyanates, nitric acid, perchlorates, permanganates, percoxides, sodium peroxide, sulfuric acid, uranium fluoride may generate electrostatic charges due to low conductivity Alcohols are incompatible with strong acids, acid chlorides, acid anhydrides, oxidising and reducing agents. reacts violently, with alkaline metals and alkaline earth metals to produce hydrogen react with strong acids, strong caustics, aliphatic amines, isocyanates, acetaldehyde, benzoyl peroxide, chromic acid, chromium oxide, dialkylzincs, dichlorine oxide, ethylene oxide, hypochlorous acid, isopropyl chlorocarbonate, lithium tetrahydroaluminate, nitrogen dioxide, pentafluoroguanidine, phosphorus halides, phosphorus pentasulfide, tangerine oil, triethylaluminium, triisobutylaluminium should not be heated above 49 deg. C. when in contact with aluminium equipment |

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

| INGREDIENT DATA | | | | | | | |
|------------------------------|------------------|-----------------|---------------------|---------------------|---------------|---------------|--|
| Source | Ingredient | Material name | TWA | STEL | Peak | Notes | |
| Australia Exposure Standards | iso-amyl alcohol | Isoamyl alcohol | 100 ppm / 361 mg/m3 | 452 mg/m3 / 125 ppm | Not Available | Not Available | |
| Ingredient | Original IDLH | | | Revised IDLH | | | |
| iso-amyl alcohol | 500 ppm | | | Not Available | | | |

Exposure controls

| Appropriate engineering controls | Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure. For flammable liquids and flammable gases, local exhaust ventilation or a process enclosure ventilation system may be required. | | |
|---|---|--|--|
| Individual protection measures, such as personal protective equipment | | | |
| Eye and face protection | Safety glasses with side shields. Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent] Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. | | |
| Skin protection | See Hand protection below | | |
| Hands/feet protection | Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended. Suitability and durability of glove type is dependent on usage. | | |
| Body protection | See Other protection below | | |
| Other protection | Overalls. PVC Apron. PVC protective suit may be required if exposure severe. Eyewash unit. Ensure there is ready access to a safety shower. Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity. For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets). Non sparking safety or conductive footwear should be considered. Conductive footwear describes a boot or shoe with a sole made from a conductive compound chemically bound to the bottom components, for permanent control to electrically ground the foot an shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds. Electrical resistance must range between 0 to 500,000 ohms. Conductive should be stored in lockers close to the room in which they are worn. Personnel who have been issued conductive footwear should not wear them from their place of work to their homes and return. | | |

Respiratory protection

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

| Required Minimum Protection Factor | Half-Face Respirator | Full-Face Respirator | Powered Air Respirator |
|------------------------------------|----------------------|----------------------|------------------------|
| up to 10 x ES | A-AUS / Class 1 | - | A-PAPR-AUS / Class 1 |
| up to 50 x ES | Air-line* | - | - |
| up to 100 x ES | - | A-3 | - |
| 100+ x ES | - | Air-line** | - |

* - Continuous-flow; ** - Continuous-flow or positive pressure demand

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

+ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.

The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.

Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance Colourless flammable liquid; slightly soluble in water (41 mg/l). Disagreeable odour. Mixes with alcohol, ether, chloroform and glacial acetic acid.

| Physical state | Liquid | Relative density (Water = 1) | 0.82-0.832 |
|---|-----------------|--|----------------|
| Odour | Not Available | Partition coefficient n-octanol / water | Not Available |
| Odour threshold | Not Available | Auto-ignition temperature (°C) | 347 |
| pH (as supplied) | Not Applicable | Decomposition temperature (°C) | Not Available |
| Melting point / freezing point (°C) | - 117.2 | Viscosity (cSt) | Not Available |
| Initial boiling point and boiling range (°C) | 132 | Molecular weight (g/mol) | 88.15 |
| Flash point (°C) | 39-45 | Taste | Not Available |
| Evaporation rate | 0,2 BuAc=1 | Explosive properties | Not Available |
| Flammability | Flammable. | Oxidising properties | Not Available |
| Upper Explosive Limit (%) | 10.0 | Surface Tension (dyn/cm or mN/m) | Not Available |
| Lower Explosive Limit (%) | 1.9 | Volatile Component (%vol) | 100 |
| Vapour pressure (kPa) | 0.27 @ 20C | Gas group | Not Available |
| Solubility in water | Partly miscible | pH as a solution (1%) | Not Applicable |
| Vapour density (Air = 1) | 3.0 | VOC g/L | Not Available |
| Heat of Combustion (kJ/g) | Not Available | Ignition Distance (cm) | Not Available |
| Flame Height (cm) | Not Available | Flame Duration (s) | Not Available |
| Enclosed Space Ignition Time Equivalent (s/m3) | Not Available | Enclosed Space Ignition Deflagration Density (g/m3) | Not Available |

SECTION 10 Stability and reactivity

| Reactivity | See section 7 |
|---------------------------------------|--|
| Chemical stability | Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur. |
| Possibility of hazardous reactions | See section 7 |
| Conditions to avoid | See section 7 |
| Incompatible materials | See section 7 |
| Hazardous decomposition products | See section 5 |

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful. The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhaled Adult volunteers exposed to primary isoamyl alcohol at 100 ppm for 3 to 5 minutes showed ocular and upper respiratory tract irritation Aliphatic alcohols with more than 3-carbons cause headache, dizziness, drowsiness, muscle weakness and delirium, central depression, coma, seizures and behavioural changes. Secondary respiratory depression and failure, as well as low blood pressure and irregular heart rhythms, may follow. Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, fatigue and inco-ordination.

| Ingestion | Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual. Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733) Overexposure to non-ring alcohols causes nervous system symptoms. These include headache, muscle weakness and inco-ordination, giddiness, confusion, delirium and coma. Ingestion of 30 ml of primary isoamyl alcohol was lethal for adults. Half the rabbits given an oral dose of 0.7 g/kg primary isoamyl alcohol | | | |
|--|--|---|--|--|
| | showed stupour and loss of voluntary movement. | Considered an unlikely route of entry in commercial/industrial environments. The liquid may produce gastrointestinal discomfort and may be narmful if swallowed. | | |
| Skin Contact | Repeated exposure may cause skin cracking, flaking or drying following normal handling and use. There is some evidence to suggest that the material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering. Most liquid alcohols appear to act as primary skin irritants in humans. Significant percutaneous absorption occurs in rabbits but not apparently in man. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. | | | |
| Eye | Ingestion of 30 ml of primary isoamyl alcohol was lethal for adults. Half the rabbits given an oral dose of 0.7 g/kg primary isoamyl alcohol showed stupour and loss of voluntary movement. There is some evidence that material may produce eye irritation in some persons and produce eye damage 24 hours or more after instillation. Moderate inflammation may be expected with redness; conjunctivitis may occur with prolonged exposure. | | | |
| Chronic | Long-term exposure to respiratory irritants may result Prolonged or repeated skin contact may cause drying Substance accumulation, in the human body, may or exposure. Animal testing shows that primary isoamyl alcohol m forestomach. Chronic solvent inhalation exposures may result in ne | g with cracking, irritation and possib ocur and may cause some concern ay cause cancer, including myeloid | le dermatitis following. ollowing repeated or long-term occupational leukaemia, liver cell cancer and cancer of the | |
| | ΤΟΧΙCΙΤΥ | IRRITATION | | |
| | Dermal (rabbit) LD50: 3212 mg/kg ^[2] | Eye (Human): | 50ppm | |
| | | | rabbit): 20mg/24H - Moderate | |
| ISO-AMYL ALCOHOL | | | ffect observed (irreversible damage) ^[1] | |
| | | | rabbit): 20mg/24H - Moderate | |
| | | | ffect observed (irritating) ^[1] | |
| Legend: | 1. Value obtained from Europe ECHA Registered Su specified data extracted from RTECS - Register of To | | btained from manufacturer's SDS. Unless otherwise | |
| | | | | |
| ISO-AMYL ALCOHOL | Olfaction effects, conjunctival irritation, antipsychotic changes recorded. Asthma-like symptoms may continue for months or e condition known as reactive airways dysfunction symcompound. Main criteria for diagnosing RADS includ of persistent asthma-like symptoms within minutes to include a reversible airflow pattern on lung function triand the lack of minimal lymphocytic inflammation, wi disorder with rates related to the concentration of and is a disorder that occurs as a result of exposure due reversible after exposure ceases. The disorder is charter and the lack of minimal symptoms within after prolonger production of vesicles, scaling and thickening of the SThe Branched Chain Saturated Alcohol (BCSA) grou low acute toxicity. Following repeated application, see In humans, no evidence of skin irritation was found a severe eye irritation. As current levels encountered to low potential to cause sensitization. For individuals wexpected to cause light-mediated toxicity or allergy. | even years after exposure to the ma drome (RADS) which can occur afte le the absence of previous airways of bours of a documented exposure of ests, moderate to severe bronchial ithout eosinophilia. RADS (or asthm d duration of exposure to the irritatin to high concentrations of irritating s aracterized by difficulty breathing, c d or repeated exposure and may pri- skin. up of fragrance ingredients was eval ven materials had low whole-body to at concentrations of 2-10%. Undilute during use are low, eye irritation is u who are already sensitized, an elicitation | terial ends. This may be due to a non-allergic or exposure to high levels of highly irritating disease in a non-atopic individual, with sudden onset o the irritant. Other criteria for diagnosis of RADS hyperreactivity on methacholine challenge testing, a) following an irritating inhalation is an infrequent g substance. On the other hand, industrial bronchitis ubstance (often particles) and is completely bugh and mucus production. boduce on contact skin redness, swelling, the uated for safety. The fifteen materials tested have boxicity. d, 11 materials evaluated caused moderate to hikely during routine use. The materials have no or | |
| ISO-AMYL ALCOHOL | changes recorded. Asthma-like symptoms may continue for months or e condition known as reactive airways dysfunction sym compound. Main criteria for diagnosing RADS includ of persistent asthma-like symptoms within minutes to include a reversible airflow pattern on lung function tt and the lack of minimal lymphocytic inflammation, wi disorder with rates related to the concentration of and is a disorder that occurs as a result of exposure due reversible after exposure ceases. The disorder is cha The material may cause skin irritation after prolonger production of vesicles, scaling and thickening of the s The Branched Chain Saturated Alcohol (BCSA) grou low acute toxicity. Following repeated application, se In humans, no evidence of skin irritation was found a severe eye irritation. As current levels encountered d low potential to cause sensitization. For individuals w expected to cause light-mediated toxicity or allergy. | even years after exposure to the ma drome (RADS) which can occur afte le the absence of previous airways of bours of a documented exposure of ests, moderate to severe bronchial ithout eosinophilia. RADS (or asthm d duration of exposure to the irritatin to high concentrations of irritating s aracterized by difficulty breathing, c d or repeated exposure and may pri- skin. up of fragrance ingredients was eval ven materials had low whole-body to at concentrations of 2-10%. Undilute during use are low, eye irritation is u who are already sensitized, an elicitation | terial ends. This may be due to a non-allergic or exposure to high levels of highly irritating disease in a non-atopic individual, with sudden onset o the irritant. Other criteria for diagnosis of RADS hyperreactivity on methacholine challenge testing, a) following an irritating inhalation is an infrequent g substance. On the other hand, industrial bronchitis ubstance (often particles) and is completely bugh and mucus production. boduce on contact skin redness, swelling, the uated for safety. The fifteen materials tested have boxicity. d, 11 materials evaluated caused moderate to hikely during routine use. The materials have no or | |
| | changes recorded. Asthma-like symptoms may continue for months or e condition known as reactive airways dysfunction sym compound. Main criteria for diagnosing RADS includ of persistent asthma-like symptoms within minutes to include a reversible airflow pattern on lung function te and the lack of minimal lymphocytic inflammation, wi disorder with rates related to the concentration of anis is a disorder that occurs as a result of exposure due reversible after exposure ceases. The disorder is cha The material may cause skin irritation after prolonged production of vesicles, scaling and thickening of the s The Branched Chain Saturated Alcohol (BCSA) grou low acute toxicity. Following repeated application, se In humans, no evidence of skin irritation was found a severe eye irritation. As current levels encountered d low potential to cause sensitization. For individuals w expected to cause light-mediated toxicity or allergy. Testing has not shown this group of materials to caus | even years after exposure to the ma drome (RADS) which can occur afte le the absence of previous airways of bours of a documented exposure to ests, moderate to severe bronchial thout eosinophilia. RADS (or asthm d duration of exposure to the irritatin to high concentrations of irritating s aracterized by difficulty breathing, c d or repeated exposure and may pre- skin. up of fragrance ingredients was eval ven materials had low whole-body to at concentrations of 2-10%. Undilute furing use are low, eye irritation is u who are already sensitized, an elicita se genetic toxicity. | terial ends. This may be due to a non-allergic or exposure to high levels of highly irritating disease in a non-atopic individual, with sudden onset o the irritant. Other criteria for diagnosis of RADS hyperreactivity on methacholine challenge testing, a) following an irritating inhalation is an infrequent by substance. On the other hand, industrial bronchitis ubstance (often particles) and is completely ough and mucus production. bduce on contact skin redness, swelling, the uated for safety. The fifteen materials tested have poicity. d, 11 materials evaluated caused moderate to hikely during routine use. The materials have no or tion reaction is possible. The BCSA are not | |
| Acute Toxicity | changes recorded. Asthma-like symptoms may continue for months or e condition known as reactive airways dysfunction sym compound. Main criteria for diagnosing RADS includ of persistent asthma-like symptoms within minutes to include a reversible airflow pattern on lung function to and the lack of minimal lymphocytic inflammation, wi disorder with rates related to the concentration of and is a disorder that occurs as a result of exposure due reversible after exposure ceases. The disorder is cha The material may cause skin irritation after prolonger production of vesicles, scaling and thickening of the 3 The Branched Chain Saturated Alcohol (BCSA) grou low acute toxicity. Following repeated application, se In humans, no evidence of skin irritation was found a severe eye irritation. As current levels encountered d low potential to cause sensitization. For individuals w expected to cause light-mediated toxicity or allergy. Testing has not shown this group of materials to caus | even years after exposure to the ma drome (RADS) which can occur afte le the absence of previous airways of bours of a documented exposure of ests, moderate to severe bronchial thout eosinophilia. RADS (or asthm to high concentrations of irritating s aracterized by difficulty breathing, c d or repeated exposure and may pre- skin. up of fragrance ingredients was eval ven materials had low whole-body to the concentrations of 2-10%. Undilute during use are low, eye irritation is u who are already sensitized, an elicita se genetic toxicity. Carcinogenicity | erial ends. This may be due to a non-allergic or exposure to high levels of highly irritating disease in a non-atopic individual, with sudden onset o the irritant. Other criteria for diagnosis of RADS hyperreactivity on methacholine challenge testing, a) following an irritating inhalation is an infrequent g substance. On the other hand, industrial bronchitis ubstance (often particles) and is completely ough and mucus production. bduce on contact skin redness, swelling, the uated for safety. The fifteen materials tested have oxicity. d, 11 materials evaluated caused moderate to nlikely during routine use. The materials have no or tion reaction is possible. The BCSA are not | |
| Acute Toxicity Skin Irritation/Corrosion Serious Eye | changes recorded. Asthma-like symptoms may continue for months or e condition known as reactive airways dysfunction sym compound. Main criteria for diagnosing RADS includ of persistent asthma-like symptoms within minutes to include a reversible airflow pattern on lung function to and the lack of minimal lymphocytic inflammation, wi disorder with rates related to the concentration of and is a disorder that occurs as a result of exposure due reversible after exposure ceases. The disorder is cha The material may cause skin irritation after prolonged production of vesicles, scaling and thickening of the s The Branched Chain Saturated Alcohol (BCSA) grou low acute toxicity. Following repeated application, se In humans, no evidence of skin irritation was found a severe eye irritation. As current levels encountered d low potential to cause sensitization. For individuals w expected to cause light-mediated toxicity or allergy. Testing has not shown this group of materials to caus | even years after exposure to the ma drome (RADS) which can occur afte le the absence of previous airways of bours of a documented exposure l ests, moderate to severe bronchial thout eosinophilia. RADS (or asthm d duration of exposure to the irritatin to high concentrations of irritating s aracterized by difficulty breathing, cr d or repeated exposure and may pre- skin. up of fragrance ingredients was eval wen materials had low whole-body that concentrations of 2-10%. Undilute during use are low, eye irritation is u who are already sensitized, an elicita se genetic toxicity. Carcinogenicity Reproductivity | A transformation of the second seco | |

SECTION 12 Ecological information

Toxicity

| ISO-AMYL ALCOHOL | Endpoint | Test Duration (hr) | Species | Value | Source |
|------------------|-----------|--------------------|-------------------------------|----------|--------|
| | EC50 | 72h | Algae or other aquatic plants | 113mg/l | 2 |
| | EC50 | 48h | Crustacea | >120mg/l | 2 |
| | NOEC(ECx) | 72h | Algae or other aquatic plants | 29mg/l | 2 |

| | LC50 | 96h | Fish | >120mg/l | 2 |
|---------|-----------------|-----|--|----------|---|
| | EC50 | 96h | Algae or other aquatic plants | 181mg/l | 1 |
| Legend: | Ecotox database | | ed Substances - Ecotoxicological Information - Aq ard Assessment Data 6. NITE (Japan) - Bioconcei | | |

BOD 5 if unstated: 0.162,59% COD : 77%

DO NOT discharge into sewer or waterways.

Persistence and degradability

| Ingredient | Persistence: Water/Soil | Persistence: Air |
|---------------------------|--------------------------|------------------|
| iso-amyl alcohol | LOW | LOW |
| Bioaccumulative potential | | |
| Ingredient | Bioaccumulation | |
| iso-amyl alcohol | LOW (LogKOW = 1.16) | |
| Mobility in soil | | |
| Ingredient | Mobility | |
| iso-amyl alcohol | MEDIUM (Log KOC = 3.777) | |
| | | |

SECTION 13 Disposal considerations

| Waste treatment methods | |
|------------------------------|--|
| Product / Packaging disposal | Containers may still present a chemical hazard/ danger when empty. Return to supplier for reuse/ recycling if possible. Otherwise: If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. Where possible retain label warnings and SDS and observe all notices pertaining to the product. Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked. A Hierarchy of Controls seems to be common - the user should investigate: Reduction Recuse Recycling Disposal (if all else fails) This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate. DO NOT allow wash water from cleaning or process equipment to enter drains. It may be necessary to collect all wash water for treatment before disposal. It may be necessary to collect all wash water for treatment before disposal. Where in doubt contact the responsible authority. Recycle wherever possible. Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture |

SECTION 14 Transport information

| Labels Required | | |
|------------------------------------|--------------------|----------------|
| | | |
| Marine Pollutant | NO | |
| HAZCHEM | •3Y | |
| Land transport (ADG) | | |
| 14.1. UN number or ID number | 1105 | |
| 14.2. UN proper shipping name | PENTANOLS | |
| 14.3. Transport hazard | Class | 3 |
| class(es) | Subsidiary Hazard | Not Applicable |
| 14.4. Packing group | ш | |
| 14.5. Environmental hazard | Not Applicable | |
| 14.6. Special precautions for user | Special provisions | 223 |

Limited quantity 5 L

| Air transport (ICAO-IATA / DGR | R) | | | |
|---------------------------------------|---|-------------------|-------|--|
| 14.1. UN number | 1105 | 1105 | | |
| 14.2. UN proper shipping name | Pentanols | | | |
| | ICAO/IATA Class | 3 | | |
| 14.3. Transport hazard class(es) | ICAO / IATA Subsidiary Hazard | Not Applicable | | |
| 0.000(00) | ERG Code | 3L | | |
| 14.4. Packing group | Ш | | | |
| 14.5. Environmental hazard | Not Applicable | | | |
| | Special provisions | | A3 | |
| | Cargo Only Packing Instructions | | 366 | |
| | Cargo Only Maximum Qty / Pack | | 220 L | |
| 14.6. Special precautions for user | Passenger and Cargo Packing Instructions | | 355 | |
| 4001 | Passenger and Cargo Maximum | Qty / Pack | 60 L | |
| | Passenger and Cargo Limited Quantity Packing Instructions | | Y344 | |
| | Passenger and Cargo Limited Ma | aximum Qty / Pack | 10 L | |

Sea transport (IMDG-Code / GGVSee)

| 14.1. UN number | 1105 | | |
|---------------------------------------|--------------------|---------------------|--|
| 14.2. UN proper shipping name | PENTANOLS | | |
| 14.3. Transport hazard | IMDG Class | 3 | |
| class(es) | IMDG Subsidiary Ha | zard Not Applicable | |
| 14.4. Packing group | III | | |
| 14.5 Environmental hazard | Not Applicable | | |
| | EMS Number | F-E , S-D | |
| 14.6. Special precautions for user | Special provisions | 223 | |
| | Limited Quantities | 5 L | |
| | | | |

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

| Product name | Pollution Category | Ship Type |
|-----------------|--------------------|-----------|
| Isoamyl alcohol | Z | 3 |

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

| Product name | Group |
|----------------------------------|---------------------------|
| iso-amyl alcohol | Not Available |
| 14.7.3. Transport in bulk in acc | ordance with the IGC Code |
| Product name | Ship Type |

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

Not Available

iso-amyl alcohol is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals Australian Inventory of Industrial Chemicals (AIIC)

Additional Regulatory Information

Not Applicable

iso-amyl alcohol

National Inventory Status

| National Inventory | Status | |
|---|-----------------------|--|
| Australia - AIIC / Australia Non- Industrial Use | Yes | |
| Canada - DSL | Yes | |
| Canada - NDSL | No (iso-amyl alcohol) | |
| China - IECSC | Yes | |

| National Inventory | Status | | |
|----------------------------------|---|--|--|
| Europe - EINEC / ELINCS / NLP | Yes | | |
| Japan - ENCS | Yes | | |
| Korea - KECI | Yes | | |
| New Zealand - NZIoC | Yes | | |
| Philippines - PICCS | Yes | | |
| USA - TSCA | All chemical substances in this product have been designated as TSCA Inventory 'Active' | | |
| Taiwan - TCSI | Yes | | |
| Mexico - INSQ | Yes | | |
| Vietnam - NCI | Yes | | |
| Russia - FBEPH | Yes | | |
| Legend: | Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration. | | |

SECTION 16 Other information

| Revision Date | 15/04/2021 |
|---------------|------------|
| Initial Date | 24/04/2002 |

SDS Version Summary

| Version | Date of Update | Sections Updated |
|---------|-------------------|--|
| 7.1 | 17/09/2016 | Physical and chemical properties - Appearance, Toxicological information - Toxicity and Irritation (Other), Identification of the substance / mixture and of the company / undertaking - Use |
| 8.1 | 15/04/2021 | Expiration. Review and Update |

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

- PC TWA: Permissible Concentration-Time Weighted Average
- PC STEL: Permissible Concentration-Short Term Exposure Limit
- IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists
- STEL: Short Term Exposure Limit
- TEEL: Temporary Emergency Exposure Limit.
- IDLH: Immediately Dangerous to Life or Health Concentrations
- ES: Exposure Standard
- OSF: Odour Safety Factor
- NOAEL: No Observed Adverse Effect Level
- LOAEL: Lowest Observed Adverse Effect Level
- TLV: Threshold Limit Value
- LOD: Limit Of Detection
- OTV: Odour Threshold Value
- BCF: BioConcentration Factors
- BEI: Biological Exposure Index
- DNEL: Derived No-Effect Level
- PNEC: Predicted no-effect concentration
- AIIC: Australian Inventory of Industrial Chemicals
- DSL: Domestic Substances List
- NDSL: Non-Domestic Substances List
- IECSC: Inventory of Existing Chemical Substance in China
- EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European List of Notified Chemical Substances
- NLP: No-Longer Polymers
 ENCS: Existing and New Chemical Substances Inventory
- KECI: Korea Existing Chemicals Inventory
- NZIOC: New Zealand Inventory of Chemicals
- PICCS: Philippine Inventory of Chemicals and Chemical Substances
- TSCA: Toxic Substances Control Act
- TCSI: Taiwan Chemical Substance Inventory
- INSQ: Inventario Nacional de Sustancias Químicas
- NCI: National Chemical Inventory
- FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.